

DESIGN AND FABRICATION OF AUTOMATIC ELECTROMAGNETIC SHOCK ABSORBER

D.Mohankumar¹, Dr. M. Prem JayaKumar²
 Research Scholar¹, Supervisor, Department of Automobile Engineering,
 BIST, BIHER, Bharath university, Chennai – 73.
mohankumar.auto@bharathuniv.ac.in

Absrtract

The reason for the stun absorber over an vehicle's suspension framework may be to decrease those vehicle's vibration by dissipating the vibrational vitality. Regarding 10 a considerable length of time ago, analysts started searching under recouping those vibrational vitality utilizing. Previously, general, these frameworks fill in by main absorbing the dynamic vitality about suspension vibration the middle of those wheel and a sprung impostor. The principle point of the work will be proficiently transforming that vitality under electrical force by utilizing ideally planned control generating stun absorber. In turn, the electrical force might a chance to be. Used to revive batteries or others effective vitality capacity units instead of a chance to be scattered. The outcomes of the venture need aid swaying Furthermore recommended that. Noteworthy amount of the movement vitality might be recouped Also saved.

Keywords: Variable frequency, Linear Displacement, Electrical Power, Regenerating Shock Absorber, Battery, Electromagnets.

INTRODUCTION

At present[1-6], a large portion of the autos are utilizing a uninvolved water powered suspension. One of the primary components of pressure driven suspension is it utilizes water powered oil as a damper[7-12]. At whatever point a vehicle navigates street inconsistencies, the excitation drive from street surface is consumed by the damper. The assimilated vitality is changed over into warmth inside the damper. The vehicle body weight is bolstered by the mechanical spring joined with the damper. In any case, there are a few burdens of water powered framework[13-16].

As indicated by Gysen, water driven damper adds to natural contamination because of hose breaks and bursts, where pressure driven liquids are harmful. At that point, the water

powered frameworks are viewed as wasteful due to the required ceaselessly pressurized framework[17-24]. In actuality, electromagnetic suspension frameworks (EMS) not require water driven liquid. It comprises of sets of changeless magnet and arrangement of current curl.

Each of them can either go about as interpreter or static armature. The collaboration between lasting magnet flux and voltage provided armature winding will bring about development or push on the interpreter. Tubular straight engine is reasonable in planning electromagnetic suspension framework because of it have a generally high constrain thickness that can control the vehicle body vibration same as water driven damper. A few inquiries about have been led to concentrate the execution of tubular direct engine[25-34]. Wang has given a definite investigation on tubular straight perpetual magnet machines. In their paper, the investigative strategy is utilized to set up the attractive field dispersion inside the machine, and the outcomes are confirmed by utilizing limited component examination[35-41].

They additionally express that foreseeing the attractive field dissemination by utilizing logical technique is more proficient contrasted with by utilizing identical circuit strategy. This is because of the issues connected with model incorrectness, especially when flux spillage is noteworthy and the flux ways are perplexing. Diagnostic arrangement is finished by utilizing barrel shaped organize framework[42-49].

The diagnostic strategy is done on different topologies of straight machine, Axial and spiral charge design, air-cored and press cored

armature. Parameters like push constrain and attractive field thickness are computed by utilizing expository arrangement and afterward contrasted and limited component investigation, while curl inductance and armature response field are ascertained by utilizing logical arrangement as it were. The distinction between scientific arrangement and limited component arrangement are little not surprisingly[50-56].

Bianchietal have concentrated the examination between every one of the setups of tubular straight engine. Different arrangements of direct engine, for example, covered and surface changeless magnet inside the rotor, air-cored and press cored armature, and moving armature or rotor. Analytical arrangements is utilized by them to analyze the execution of the considerable number of designs. Direct engine parameters, for example, attractive flux thickness, electrical and warm conditions, push constrain, and drive thickness were produced for all the straight engine designs. The outcome is then contrasted and limited component technique and the two were in understanding. Be that as it may, the unwavering quality of straight engine as suspension frameworks is constrained by presence of cogging power inside the engine.

Pauli desetal. expressed that cogging power in direct engine will influence the execution of it by decreasing its speed control precision and smoothness of straight development. They likewise portrayed the cogging power inside the engine by utilizing limited component examination and the figured out how to produce the connections between cogging power and shaft pitch. The controllable constrain in direct engine permits specialists to apply it into vehicle suspension framework in which it is called an EMS.

Goldner proposed electromagnetic safeguards to change the vitality disseminated in safeguards into electrical power. Gupta has concentrated the accessible vitality from safeguards as autos and trucks are rolled over different sorts of

streets. Graves concentrated electromagnetic regenerative damping.

They specify that vitality recovery is little and might be applicable just for electric vehicles. They likewise propose approaches to open up the movement of the stun keeping in mind the end goal to increment recoverable vitality which then again may negatively affect vehicle flow. Another intriguing perception made by them is that gadget yield voltage must be sufficiently vast to defeat the obstruction capability of the capacity gadget.

OBJECTIVE AND SCOPE OF WORK

The goal of this venture is to produce the vehicle smooth development through the creation of Magnetic Shock Absorber course of action. Presently day's vehicle utilization is expanded, so this venture is utilized to produce smooth development keeping in mind the end goal to remunerate the vehicle use.

COMPONENTS AND DESCRIPTION

An EM Shock has been created. The stun comprises of three gatherings: the changeless magnet get together, the curl get together, and the case get together. Voltage is instigated in the stun windings when the curl get together moves with respect to the magnet gatherings. The case get together adjusts and empowers the cylinder like movement between the loop and magnet congregations.



GENERATOR DESIGN

The magnet get together comprises of an inward magnet stack encompassed concentrically by a bigger measurement external magnet stack. Every stack comprises of three pivotally charged ring magnets isolated by two iron-shaft rings and two extra post rings situated at the closures of the stack. Sintered anisotropic lasting magnets are utilized. The extremity of the magnets is picked with the end goal that spiral attractive flux exudes from both sides of every iron shaft and the flux of the inward post rings includes that of the external rings.

Voltage Generation:




To first order, the magnetic flux from the magnet assembly radially penetrates each coil section over the height of the pole ring, $h = 10$ mm. Thus, for coils with $n = 8.26$ turns/mm moving axially with a velocity v past a stationary pole emanating flux density, B_i , a voltage,

$$\bullet V = n h v B_i$$

DAMPING FORCE

When a straight wire of length $L(m)$ conducts a current, $I(A)$, and is subject to a magnetic field, $B_i(T)$, normal to the wire, a force, $F(N)$, is exerted on the wire of magnitude $\bullet F = I L B_i$. An electromagnet is a type of magnet in which the magnetic field is produced by a flow of electric current. The magnetic field disappears when the current ceases. An electromagnet is a magnet that runs on electricity.

Dissimilar to a perpetual magnet, the quality of an electromagnet can without much of a stretch be changed by changing the measure of electric current that moves through it. The shafts of an electromagnet can even be switched by turning around the stream of power. An electromagnet works on the grounds that an electric current delivers an attractive field. The attractive field created by an electric current structures hovers around the electric current, as appeared in the chart given underneath.



1. (a) Conventional passive suspension system. (b) Electromagnetic suspension system.

SHOCK ABSORBER

A shock absorber is a mechanical device designed to smooth out or damp shock impulse, and dissipate kinetic energy. It is a type of dashpot.

NOMENCLATURE:

Different names for a safeguard incorporate damper and dashpot. The car suspension segment is frequently called just a shock absorber. Amid the mid twentieth century in the U.S., the then-understood Houdaille mark (purported WHO-color) was in a few places a genericized trademark for the device, but has since vanished from utilize.

DESCRIPTION:

Pneumatic and pressure driven safeguards incorporate pads and springs. A car safeguard contains spring-stacked check valves and openings to control the stream of oil through an inner cylinder.

Types Of Shock Absorber

There are various distinctive strategies for changing over an effect impact into generally smooth padded contact.

- Metal Spring
- Rubber Buffer
- Hydraulic Dashpot
- Collapsing safety Shock Absorbers
- Pneumatic Cylinders
- Self compensating Hydraulic

Diode Bridge

A diode scaffold is a course of action of (at least four) diodes in an extension circuit arrangement that gives a similar extremity of yield for either extremity of information. At the point when utilized as a part of its most normal application, for change of an exchanging current (AC) contribution to direct current a (DC) yield, it is known as an extension rectifier. An extension rectifier gives full-wave amendment from a two-wire AC input, bringing about lower cost and weight when contrasted with a rectifier with a 3-wire contribution from a transformer with an inside tapped optional winding.

The essential feature of a diode bridge is that the polarity of the output is the same regardless of the polarity at the input. The diode bridge circuit is also known as the Graetz circuit after its inventor, physicist Leo Graetz.

Application

- For automobile application
- Industrial application

Advantages

- Shock absorber cost will be less.
- Free from wear adjustment.
- Less power consumption
- Less skill technicians is sufficient to operate.
- It gives simplified very operation.
- Installation is simplified very much.
- To avoid other burnable interactions viz...(Diaphragm) is not used.
- Less time and more profit.

CONCLUSION:

The improvement of a wide range of electromagnetic suspension and its recovery properties are checked on in this paper. For latent electromagnetic suspension, it not requires outer control framework to change the damping coefficient to keep up traveler solace and steadiness. By and large the damping power is specifically direct with relative speed between sprung mass (auto body) and sprung mass (auto tire).

Consequently, the power utilization for detached electromagnetic suspension framework is far low contrasted with semi-dynamic and completely dynamic electromagnetic suspension framework. Lamentably, as far as drive thickness, detached electromagnetic suspension is the most minimal of all, along these lines uninvolved EMS alone is insufficient to give craved solace to traveler. Semi dynamic suspension framework contains both the

completely dynamic and uninvolved components along these lines making it more dependable from latent EMS yet marginally awful than dynamic EMS because of its inactive properties. MR damper is utilized as of late in semi-dynamic EMS. In any case, a few investigates have proposed a fluidless variant of semi-dynamic EMS to be connected in lightweight vehicle. Dynamic suspension framework utilizes outer control framework to control the damping power, in this manner enhancing the traveler solace and soundness.

Sadly, dynamic suspension framework expends a considerable measure of force and the structure is perplexing to plan. In any case, this paper highlights the unwavering quality of dynamic suspension framework to be connected in the lightweight vehicle. The improved mode for inactive EMS and semi-dynamic EMS might be should be possible in future keeping in mind the end goal to make their execution comparable to completely dynamic EMS in this way can be connected on lightweight vehicle. The regenerative properties of electromagnetic suspension are compressed. With change of innovation, a completely dynamic suspension may get to be distinctly one of promising patterns of dynamic suspension.

This machine was fabricated successfully and tested. It works satisfactorily. We hope that this will be one among the most versatile and interchangeable one even in future.

References

1. Meghraj P. Arekar, Swapnil Shahade, "Power Generating Shock Absorber", International Journal of Innovative Research in Science, Engineering and Technology, Volume 4, Special Issue 3, March 2015, ISSN (Print): 2347 – 6710.
2. Sethu Prakash S, Nidhin Abraham Mammen & Steve John, "Regenerative Shock Absorber", International Journal of Science, Technology & Management, Volume No 04, Special Issue No. 01, March 2015, ISSN (online): 2394-1537.
3. K.M.Afzal & A.P.Tadamalle, "Design & Development of a Regenerative Shock Absorber", Novateur Publications, International Journal of Innovations in Engineering Research and Technology [IJIERT], Volume 3, Issue 2, Feb.-2016, ISSN: 2394-3696.
4. John J. Wang, G.P. Penamalli, Lei Zhou, "Electromagnetic Energy Harvesting from Train Induced Railway Track Vibrations" Proceedings of the IEEE/ASME International Conference on Mechatronics and Embedded Systems Applications (MESA) 2012, pp. 29-34.
5. L. Zuo, B. Scully, J. Shestani, Y. Zhou, "Design and characterization of an electromagnetic energy harvester for vehicle suspensions" Journal of Smart Materials and Structures, 2009, Vol 19, pp. 1- 10.
6. Ramamoorthy, R., Kanagasabai, V., Kausalya, R., Impact of celebrities' image on brand, International Journal of Pure and Applied Mathematics, V-116, I-18 Special Issue, PP-251-253, 2017
7. Ramamoorthy, R., Kanagasabai, V., Vignesh, M., Quality assurance in operation theatre with reference to fortis malar hospital, International Journal of Pure and Applied Mathematics, V-116, I-14 Special Issue, PP-87-93, 2017
8. Ramya, N., Arthy, J., Honey comb graphs and its energy, International Journal of Pure and Applied Mathematics, V-116, I-18 Special Issue, PP-83-86, 2017
9. Ramya, N., Jagadeeswari, P., Proper coloring of regular graphs, International Journal of Pure and Applied Mathematics, V-116, I-16 Special Issue, PP-531-533, 2017
10. Ramya, N., Karunakaran, K., Proper, star and acyclic coloring of some graphs, International Journal of Pure and Applied Mathematics, V-116, I-16 Special Issue, PP-43-44, 2017

11. Ramya, N., Muthukumar, M., On coloring of 4-regular graphs, International Journal of Pure and Applied Mathematics, V-116, I-16 Special Issue, PP-491-494, 2017
12. Ramya, N., Muthukumar, M., On star and acyclic coloring of graphs, International Journal of Pure and Applied Mathematics, V-116, I-16 Special Issue, PP-467-469, 2017
13. Ramya, N., Pavi, J., Coloring of book and gear graphs, International Journal of Pure and Applied Mathematics, V-116, I-17 Special Issue, PP-401-402, 2017
14. Ramya, P., Hameed Hussain, J., Alteration framework for integrating quality of service in internet real-time network, International Journal of Pure and Applied Mathematics, V-116, I-8 Special Issue, PP-57-61, 2017
15. Ramya, P., Sriram, M., Tweet sarcasm: Peep, International Journal of Pure and Applied Mathematics, V-116, I-10 Special Issue, PP-231-235, 2017
16. Sabarish, R., Meenakshi, C.M., Comparision of beryllium and CI connecting rod using ansys, International Journal of Pure and Applied Mathematics, V-116, I-17 Special Issue, PP-127-132, 2017
17. Sabarish, R., Rakesh, N.L., Outcome of inserts for enhancing the heat exchangers, International Journal of Pure and Applied Mathematics, V-116, I-17 Special Issue, PP-419-422, 2017
18. Sangeetha, M., Gokul, N., Aruls, S., Estimator for control logic in high level synthesis, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-425-428, 2017
19. Sangeetha, M., Gokul, N., Aruls, S., Image steganography using a curvelet transformation, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-417-422, 2017
20. Saraswathi, P., Srinivasan, V., Peter, M., Research on financial supply chain from view of stability, International Journal of Pure and Applied Mathematics, V-116, I-17 Special Issue, PP-211-213, 2017
21. Saravana Kumar, A., Hameed Hussain, J., Expanding the pass percentage in semester examination, International Journal of Pure and Applied Mathematics, V-116, I-15 Special Issue, PP-45-48, 2017
22. Saravana, S., Arulselvi, S., AdaBoost SVM based brain tumour image segmentation and classification, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-399-403, 2017
23. Saravana, S., Arulselvi, S., Dynamic power management monitoring and controlling system using wireless sensor network, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-405-408, 2017
24. Saravana, S., Arulselvi, S., Clustered morphic algorithm based medical image analysis, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-411-415, 2017
25. Saravana, S., Arulselvi, S., Networks, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-393-396, 2017
26. Saritha, B., Chockalingam, M.P., Adsorptive removal of heavy metal chromium from aqueous medium using modified natural adsorbent, International Journal of Civil Engineering and Technology, V-8, I-8, PP-1382-1387, 2017
27. Saritha, B., Chockalingam, M.P., Adsorptive removal of brilliant green dye by modified coconut shell adsorbent, International Journal of Pure and Applied Mathematics, V-116, I-13 Special Issue, PP-211-215, 2017

28. Saritha, B., Chockalingam, M.P., Photodegradation of eriochrome black-T dye from aqueous medium by photocatalysis, International Journal of Pure and Applied Mathematics, V-116, I-13 Special Issue, PP-183-187, 2017
29. Saritha, B., Chockalingam, M.P., Photodradation of malachite green DYE using TiO_2 /activated carbon composite, International Journal of Civil Engineering and Technology, V-8, I-8, PP-156-163, 2017
30. Saritha, B., Chockalingam, M.P., Synthesis of photocatalytic composite Fe-C/TiO₂ for degradation of malachite green dye from aqueous medium, International Journal of Pure and Applied Mathematics, V-116, I-13 Special Issue, PP-177-181, 2017
31. Saritha, B., Chockalingam, M.P., Removal of heavy $\text{X}^{\text{X}}\text{l}$ from aqueous medium using modified natural adsorbent, International Journal of Pure and Applied Mathematics, V-116, I-13 Special Issue, PP-205-210, 2017
32. Saritha, B., Chockalingam, M.P., Degradation of malachite green dye using a semiconductor composite, International Journal of Pure and Applied Mathematics, V-116, I-13 Special Issue, PP-195-199, 2017
33. Sartiha, B., Chockalingam, M.P., Photocatalytic decolourisation of textile industry wastewater by TiO_2 , International Journal of Pure and Applied Mathematics, V-116, I-18 Special Issue, PP-221-224, 2017
34. Sartiha, B., Chockalingam, M.P., Study on photocatalytic degradation of Crystal Violet dye using a semiconductor, International Journal of Pure and Applied Mathematics, V-116, I-18 Special Issue, PP-209-212, 2017
35. Shanthi, E., Nalini, C., Rama, A., The effect of highly-available epistemologies on hardware and architecture, International Journal of Pharmacy and Technology, V-8, I-3, PP-17082-17086, 2016
36. Shanthi, E., Nalini, C., Rama, A., Drith: Autonomous, random communication, International Journal of Pharmacy and Technology, V-8, I-3, PP-17002-17006, 2016
37. Shanthi, E., Nalini, C., Rama, A., A case for replication, International Journal of Pharmacy and Technology, V-8, I-3, PP-17234-17238, 2016
38. Shanthi, E., Nalini, C., Rama, A., Elve: A methodology for the emulation of robots, International Journal of Pharmacy and Technology, V-8, I-3, PP-17182-17187, 2016
39. Shanthi, E., Nalini, C., Rama, A., Autonomous epistemologies for 802.11 mesh networks, International Journal of Pharmacy and Technology, V-8, I-3, PP-17087-17093, 2016
40. Sharavanan, R., Golden Renjith, R.J., Design and analysis of fuel flow in bend pipes, International Journal of Pure and Applied Mathematics, V-116, I-15 Special Issue, PP-59-64, 2017
41. Sharavanan, R., Jose Ananth Vino, V., Emission analysis of C.I engine run by diesel, sunflower oil, 2 ethyl hexyl nitrate blends, International Journal of Pure and Applied Mathematics, V-116, I-14 Special Issue, PP-403-408, 2017
42. Sharavanan, R., Sabarish, R., Design of built-in hydraulic jack for light motor vehicles, International Journal of Pure and Applied Mathematics, V-116, I-17 Special Issue, PP-457-460, 2017
43. Sharavanan, R., Sabarish, R., Design and fabrication of aqua silencer using charcoal and lime stone, International Journal of Pure and Applied Mathematics, V-116, I-14 Special Issue, PP-513-516, 2017

44. Sharmila, G., Thooyamani, K.P., Kausalya, R., A schoolwork on customer relationship management with special reference to domain 2 host, International Journal of Pure and Applied Mathematics, V-116, I-20 Special Issue, PP-199-203, 2017
45. Sharmila, S., Jeyanthi Rebecca, L., Anbuselvi, S., Kowsalya, E., Kripanand, N.R., Tanty, D.S., Choudhary, P., SwathyPriya, L., GC-MS analysis of biofuel extracted from marine algae, Der Pharmacia Lettre, V-8, I-3, PP-204-214, 2016
46. Sidharth Raj, R.S., Sangeetha, M., Data embedding method using adaptive pixel pair matching method, International Journal of Pure and Applied Mathematics, V-116, I-15 Special Issue, PP-417-421, 2017
47. Sidharth Raj, R.S., Sangeetha, M., Android based industrial fault monitoring, International Journal of Pure and Applied Mathematics, V-116, I-15 Special Issue, PP-423-427, 2017
48. Sidharth Raj, R.S., Sangeetha, M., Mobile robot system control through an brain computer interface, International Journal of Pure and Applied Mathematics, V-116, I-15 Special Issue, PP-413-415, 2017
49. Sivaraman, K., Sundarraj, B., Decisive lesion detection in digital fundus image, International Journal of Pure and Applied Mathematics, V-116, I-10 Special Issue, PP-161-164, 2017
50. Sridhar, J., Sriram, M., Cloud privacy preserving for dynamic groups, International Journal of Pure and Applied Mathematics, V-116, I-8 Special Issue, PP-117-120, 2017

