

Power Generation Using Vehicle to Grid

¹Shweta Mishra, ²Himanshu Sirohia, ³Bhaskar Sharma and

⁴Koushik Chakraborty

^{1,2,3,4}Jayoti Vidyapeeth Women's University,

Jaipur.

Abstract

As we see that the power request step by step expanding and furthermore expanding contamination level and ecological dangers, in this way, that the 21st century is moving towards green and sustainable power source. Vehicle-lattice combination (VGI) characterizes distinctive ways to deal with tie the transportation framework and the electric power framework in ways that may profit both. VGI commonly enclose vehicle-to-network (V2G), in fact it is further developed discernment with bidirectional stream of power between the vehicle and power lattice, accordingly the PEV (module electric vehicles) regarding as a capacity gadget. To such an extent that VGI frameworks could help in decarbonizes transportation, bolster stack balancing out, incorporate feasible vitality into the lattice and increment the enthusiasm for power organizations, and furthermore makes new intrigue plans for vehicle proprietors. These arrangements have been researched seriously on the paper from both the monetary and specialized perspectives and are here detailed. What's more, V2G necessities, for example, portability needs, charging stations accessibility and suitable PEV aggregative development are impeccably taken into clarification. The highlights, capacities and benefits of V2G are displayed here, alongside execution challenge. Numerous projects are controlled by the car enterprises; control age units and administration of various nations have been performed to make V2G innovation dependable for future employments. At long last, future improvements and situations have additionally been accounted for. A review of V2G (vehicle-to-framework) innovation is introduced in this paper. It's goal to feature the primary highlights, openings and requirements of V2G. Along these lines, after quickly continuing the most renowned charging strategy for PEVs, the V2G idea is presented, particularly featuring its capacity as a winning source open door for PEV proprietors.

1. Introduction

In this day and age petroleum products are the decisive vitality hotspots for both transportation fields and power age businesses. Exhaustion of petroleum derivative assets gives a reminder for finding the elective vitality hotspots for these divisions. Actually, the eventual fate of oil economy which is thought to be exceptionally tried and true by vehicle fleets on the planet isn't just unsustainable yet in addition extremely constrained. Also, consuming non-renewable energy sources produces ozone harming substances (GHGs) which profoundly influence the world environmental change. As per the report [1] the projection by Energy Information Agency (EIA) uncovers that the oil costs will generously ascend in the following two decades. In this unique situation, different endeavors identified with lessening oil utilization have risen. In the transportation area on account of the expanding ecological mindfulness and diminish the reliance on fossil sources and the emanation of ozone harming substances both, the vitality approach of numerous administrations around the globe is turn their advantage and firmly support to the development of RESs (sustainable power sources).[2] EVs is isolated into two major classes [3] as appeared in Fig. 1: PEVs (module EVs) and non-module EVs, these are vitally HEVs (mixture EVs). Furthermore, PEVs can be additionally partitioned into PHEVs (module half and half EVs) and BEVs (battery EVs). While BEVs are portrayed by the utilization of batteries to supply their electric impetus framework, PHEVs are by and large furnished with littler batteries since they utilize an interior ignition motor; this can straightforwardly drive the vehicle or potentially revive the battery on board, bringing about a stretched out versatility run contrasted with BEVs




Fig. 1: Electric Vehicles Classification

Right now, the most far reaching EVs available are HEVs and, to a lesser degree, PHEVs. Truth be told, in spite of the fact that BEVs display a few points of interest contrasted with ICEs (inward burning motor vehicles), HEVs and PHEVs, for example, positive mileage, bring down support costs and decrease outflow.[4-6]. Their use is not yet widespread; this is mainly due to the fact that their batteries are quite expensive and provide a low mobility range.

This drawback could be overcome through the exploitation of the PEV batteries by means of appropriate charging strategies. These aim to minimize PEV operating costs and, hence, to partially compensate for the higher investment costs compared to ICEs and HEVs [4]

The basic target of the V2G was to provide power in peak time. The electric vehicle owner charging their car in low load with low electric price and discharging the vehicle in peak time with higher cost so that the vehicle owner can make eloquent amount of benefit from V2G program. The EU (European Union), through its Energy and Climate Policy, has set an ambitious target of 2020: to provide, 20% of gross energy consumption from RESs.

Vehicle to Grid (V2G) communication is a system in which EVs communicate with the power grid to return energy to the grid. It will be an element in some EVs like plug-in models and is used as a power grid modulator to dynamically adjust energy demand.

A benefit of V2G is helping to maintain the grid level and acting as a sustainable power source substitute. This system could actuate the best time to charge cars batteries and enable energy flow in the adverse direction for shorter period of time when the public grid is need the power and the vehicle is not.

In spite of the positive effect of vitality approach on the planet, it additionally has a few issues that must be quickly tended to. In 2016, more than 25% of Europe has stopped the coal-consuming force plants, with course of action to end the petroleum product utilization by 2020 in Austria and 2025 in Britain. In spite of the fact that the plant on shutting will have critical impacts of bringing down CO₂ discharges, it leaves numerous nations in thinking about how they will full fill the need of vitality. As indicated by a current report by the Institution of Mechanical Engineers, Britain may confront a vitality hole of up to 55% toward the finish of 10 years. Vitality request and proficiency must be considered now with the goal that arrangements can be created preceding the aggregate loss of the power matrix. At the end of the day, the UK (among other coal-dependent nations) soon faces a vitality supply emergency, on the off chance that they don't take the correct measures. One arrangement informed to control the misfortune concerning coal as a vitality source, is to take advantage of the capability of the electric vehicle market and how the switch can be transposed to the influence lattice [7].

Much exertion must be given to achieve the future EV showcase projections as they include high introductory cost contrasted with the ICEVs. Then again, the electrification of transportation division has all the earmarks of being one of the possible answers for the difficulties, for example, worldwide environmental change, vitality security and geopolitical worries on the accessibility of petroleum products. The EVs are potential on serving the electric lattice as free disseminated vitality source. It has been uncovered by a few investigations that most vehicles are stopped very nearly 95% of their opportunity. For this

situation, they can stay associated with lattice and be prepared to convey the vitality put away in their batteries under the idea of vehicle to network (V2G) [8].

2. Concept of V2G

The Vehicle to grid integration (V2G) concept was firstly introduced by” Willet Kompton” of the Delaware University.

Vehicle-to-grid (V2G) describes a system in which there is reciprocal, bi-directional electrical energy flow between plug-in electric vehicles, such as electric cars (BEV) and plug-in hybrids (PHEV), and the power grid.




Fig. 2: Schematically Illustrates Connections between Vehicles and the Electric Power Grid

Electricity flows one-way from generators through the grid to electricity users. Electricity flows back to the grid from EDVs, or with battery EDVs, the flow is two ways (shown in Fig. as lines with two arrows). The control signal from the grid operator (labelled ISO, for Independent System Operator) could be a broadcast radio signal, or through a cell phone network, direct Internet connection, or power line carrier. In any case, the grid operator sends requests for power to a large number of vehicles.

The flag may go straightforwardly to every individual vehicle, schematically in the upper right of Fig. , or to the workplace of an armada administrator, which thus controls vehicles in a solitary parking garage, schematically appeared in the lower right of Fig. , or through an outsider aggregator of scattered individual vehicles' energy (not appeared). (The lattice administrator likewise dispatches control from customary focal station generators utilizing a voice phone call or a T1 line) Other types of V2G technology consists of load-sharing sources with the power grid. This can include subsets of V2G like vehicle-to-home (V2H) and vehicle-to-building (V2B), both of which draw power directly from the EV rather than through the power grid.[7]

3. Versions of V2G

V2G is various if battery-to-grid power applied to vehicles. There are three main different version of the vehicle-to-grid concept, all of which involve an on board battery [9]:

- A Hybrid or fuel cell vehicle, which generates power from storable fuel, uses its generator to produce power for a utility at peak electricity usage times. Here the vehicle serves as a distributed generation system, producing power from conventional fossil fuel or hydrogen.
- A battery power or plug-in hybrid vehicle which uses its excess rechargeable battery capacity to provide power to the electric grid in response to peak load demands. These vehicles recharged during off-peak time at cheaper rate while helping to absorb excess night time generation. Here the vehicle serves as a distributed battery storage system to buffer power.
- A solar vehicle which uses its excess charging capacity to provide power to the electric grid when the battery is fully charged.

V2G Requirements

PEV owners can make a profit by V2G. This will be accomplished by satisfying several requirements, among which the most important ones are that V2G operation should not impair PEVs mobility and should benefit from appropriate charging infrastructures and control & communication devices. And, last but not at least, suitable V2G architectures should be developed in order to aggregate a certain amount of PEVs. This is mandatory in order to provide some of the services previously mentioned.

- **Mobility Needs:** One of the major drawbacks to managing PEV batteries by V2G is the random nature of owners' habits and the enslavement of PEVs to the needs of the power system rather than to those of their owners. However, vehicles electrification is not going to change people's lifestyles and habits, so ICEs data could be appropriately employed [10]. The most important information concerns:
 - the number of cars on the road
 - when and where a car is parked;
 - The distance traveled.

In a study of the UK Department of Transport (UK Time Use Survey), it is reported that people mainly use their car for the home-work-home route on week days, resulting in being on the road from 7-9 am and 4-7 pm. However, even during rush hours, no more than 11% of the whole fleet is on the road. It means that at least 89% of cars are parked [11, 12]. It means that a mean trip would use approximately 10% of the SOC of a PEV characterized by 130 km range. In spite of some differences, these results are corroborated by another study regarding the US transport system, that states that 85%-90% of vehicles are parked at home, work or shopping malls, being idle for 22 h per day. Furthermore, the same study estimates that an average roundtrip commuting distance of about 50 km is covered in about 52 min. In addition, 80% of commuters travel less than 60 km per day.

A mobility modeling procedure suitable for V2G is proposed in reference [13]. A generic PEV fleet is split into three sub-fleets: The first is made up of all the

PEVs on the road; the second consists of all PEVs parked and plugged in, whereas the last one groups all PEVs that are parked and unplugged

Charging Stations

PEV batteries misuse by V2G will unequivocally rely upon the sum and appropriation of charging stations. Truth be told, proper arranging of the charging stations conveyance will build PEV accessibility for V2G purposes, making V2G more adaptable and dependable in the meantime, V2G-innovation works through uncommonly planned bi-directional charging stations. These charging stations enable electric vehicles proprietors to charge their autos while likewise encouraging the release of the vehicle's battery. The pilot has been propelled to test the suitability of releasing electric vehicles to help adjust the free market activity inside the power matrix [14].




Fig. 3: How Vehicle-to-grid (V2G) works

- V2G Architectures

Two main V2G architectures [15]:

- Description of the direct, deterministic architecture
- Description of the aggregative architecture

The deterministic architecture shown in Fig.4 in which V2G is provided by each PEV autonomously, directly controlled and linked to the system operator by communication and power lines.




Fig. 4: A V2G Deterministic Architecture

The second one (aggregative design) comprises of a structure giving V2G by methods for a PEV armada, as appeared in Fig. 5.

The principal arrangement would have all the earmarks of being straightforward and simple to actualize, however it keeps V2G from giving a few administrations that require high power and vitality least edges. Contrariwise, an aggregative system does not keep V2G from conveying any administrations, but rather presents extra expenses.




Fig. 5: V2G Aggregative Architecture

The option aberrant V2G framework engineering includes a few aggregators as appeared in Fig. In such manner, every aggregator totals the subordinate administrations gave by singular EVs to make a solitary controllable power asset. This design is aberrant as aggregators are middle of the road between the vehicles and the matrix administrator. The aggregator gets auxiliary administration demands from the lattice framework administrator and issues charging or releasing summons to contracted vehicles. The accessibility and dependability of these V2G designs in giving subordinate administrations is evaluated. It has been demonstrated that the accessibility and unwavering quality achievable by methods for the deterministic V2G engineering is around 92% and 95% in the best cases, individually. A total of PEVs will be required keeping in mind the end goal to take an interest in the vitality advertise [16]. Truth be told, two distinctive methodologies can be taken after: fetched work based power drawn booking and value delicate vitality offering. The first, which is reasonable for the deterministic V2G design, comprises in setting up the PEV charging profile based on the vitality value given by the day-ahead market and in refreshing it progressively. Thus, each PEV is in charge of its charging without impedance from the framework administrator: in the hours of least expensive costs, the PEV ought to energize at its greatest rate. Since the aggregative V2G design would have all the earmarks of being the most encouraging one, a few investigations have been done intending to characterize

the part and undertakings of this structure, which is likewise characterized aggregator. Its part might go about as a delegate between each PEV proprietor and the framework administrator [6, 8, 16, 17 and 18]

The aggregator will have the capacity to buy vitality more inexpensively than a solitary PEV proprietor, in this way its benefits will comprise of a pre-set offer of all the income originating from the vitality sold and the V2G administrations gave.

4. Future Scenarios

EVs

The main features of future EVs cannot be precisely stated as they will depend on many technical, economic, environmental and social issues. It appears plausible that many EVs models will be available to match different owners' needs and electric grid requirements. There is innate framework esteem in offering the adaptability of an EV battery. The pilot plans to examine how people can not just make an undeniable commitment to the earth by decreasing CO₂ outflows, yet in addition gain cash - denoting the beginning of a genuine vitality upheaval in the field of electric driving. What's more, enhancements in battery innovation will empower EVs to broaden their range. On this point, it is normal that BEVs will have a scope of 160 km in any event [3]. Furthermore, the PEVs batteries capacity and power will be up to 70 kWh and 20 kW respectively, and batteries will be fully recharged in 8-12 h or less [16 and 20]. Assuming PEVs as one of the main elements of future power systems, four steps of evolution can be considered, as shown in Fig.6.




Fig. 6: Four Steps of Evolution for EVs

The first concerns the EVs accessible today; being in their earliest stages, they cannot be as develop as ICEs, but rather they can give critical inputs to makers to coordinate further and future research. The second era of EVs will be basically in view of the first, yet battery control and proficiency will be improved so as to build their range and decline their expenses. Likewise, regardless of whether control ability will continue as before, correspondence capacity will be enhanced keeping in mind the end goal to actualize more advanced charging methodologies. Therefore, second era EVs will have the

capacity to give subordinate administrations by G2V generally [3]. Considerably unique in relation to the initial two ages will be the third one, since EVs will be described by high appraised control and a bidirectional power stream charger. It is normal that charging will be performed at 50-100 kW, essentially lessening the revive time. The bidirectional vitality stream will enable EVs to work V2G at a simple level [3]. At last, EVs of the fourth era will have a noteworthy V2G capacity. They will likewise be outfitted with a progressed and dependable correspondence framework, ensuring their total [16].

V2G

V2G will be essentially dictated by giving subordinate administrations; nonetheless, it is sensible to expect that the benefits will diminish as the quantity of PEVs giving such sort of administrations increment, prompting market immersions. In such manner, a near report on the Texas control framework [18]. In this examination, the impacts of both G2V and V2G on subordinate administration markets are considered. In view of G2V offering limit, a drop of 70% of the subordinate administrations advertise cost has been assessed for only 300,000 PEVs, i.e., an offer of just 1.5% of the 20 million enrolled vehicles in Texas. A similar value lessening is accomplished with only 100,000 PEVs giving V2G administrations. Subsequently, obviously showcase immersion could be achieved rapidly [18], notwithstanding, advertise immersion could be accomplished even before the payback era. In spite of the fact that the examination alludes to the direction showcase just, it indicates how the execution of V2G requires cautious financial assessment, perhaps considering new administrations that V2G ought to give.

5. Conclusion

Even with a quickly changing power commercial center, PEVs may assume a huge part as a vitality/limit asset. Development as of now occurring in the business incorporate cost responsive request advancing out of interest side support; A wide utilization of PEVs will bring numerous advantages, yet it might cause a few downsides as well. Picking suitable PEV administration procedures will be required keeping in mind the end goal to limit PEVs working expenses and their effect on the power framework. Specifically, V2G is particularly productive in giving subordinate administrations, for example, stack leveling, control and save. These are for the most part changing the network into a framework in which variable request as opposed to variable age will be depended upon to adjust the lattice. In a universe of across the board PEV appropriation, PEVs might be the biggest and most adaptable loads on the framework. This examination of the writing uncovers that diverse approaches to perform V2G exist. Thus, the most reasonable one ought to be deliberately picked based on an all encompassing investigation, which relies upon particular objectives and nearby situations and considers specialized, financial, arranging and versatility perspectives.

References

- [1] International energy outlook 2011: Energy Information Administration (EIA), Office of Integrated Analysis and Forecasting, U.S. Department of Energy, Washington, DC (2011).
- [2] Journal of Energy and Power Engineering 8 (2014) 152-165 .Vehicle-to-Grid Technology: State-of-the-Art and Future Scenarios.
- [3] Tuttle D.P., Baldick R., The evolution of plug-in electric vehicle-grid interactions, IEEE Trans. Smart Grid 3(1) (2012), 500-505.
- [4] De Los Rios A., Goentzel J., Nordstrom K.E., Siegert C.W., Economic analysis of vehicle-to-grid (V2G)-enabled fleets participating in the regulation service market, Proc. IEEE Innovative Smart Grid Technologies Conference (2012), 1-8.
- [5] Weiller C., Plug-in hybrid electric vehicle impacts on hourly electricity demand in the united states, Energy Policy 39(6) (2011), 3766-3778.
- [6] Keiser J., Glass J., Masuch N., Lutzenberger M., Albayrak S., A distributed multi-operator W2V2G management approach, in: Proc. IEEE International Conference on Smart Grid Communications (2011), 273-278.
- [7] The Latest in Vehicle to Grid (V2G) Charging By Eric Schmidt
- [8] Kempton W., Letendre S., Electric vehicles as a new power source for electric utilities, J Transp Res Part D 2(3) (1997), 157–175.
- [9] <https://en.wikipedia.org/wiki/Vehicle-to-grid#Versions>
- [10] Shahidinejad S., Filizadeh S., Bibeau E., Profile of charging load on the grid due to plug-in vehicles, IEEE Trans. Smart Grid 3(1) (2012), 135-141.
- [11] Berthold F., Blunier B., Bouquain D., Williamson S., Miraoui A., PHEV control strategy including vehicle to home (V2H) and home to vehicle (H2V) functionalities, Proc. IEEE Vehicle Power and Propulsion Conference (2011).
- [12] Ma Y., Houghton T., Cruden A., Infield D., Modeling the benefits of vehicle-to-grid technology to a power system, IEEE Trans. Power Syst. 27(2) (2012), 1012-1020.
- [13] Damiano A., Marongiu I., Porru M., Serpi A., Electric vehicle energy storage management for renewable energy sources exploitation, Proc. IEEE International Electric Vehicle Conference (2012), 1-8.

- [14] <https://newmotion.com/en/drive-electric/v2g-charging-next-generation-technology>
- [15] Quinn C., Zimmerle D., Bradley T.H., The effect of communication architecture on the availability, reliability, and economics of plug-in hybrid electric vehicle-to-grid ancillary services, *Journal of Power Sources* 195(5) (2010), 1500-1509.
- [16] Guille C., Gross G., A conceptual framework for the vehicle-to-grid (V2G) implementation, *Energy Policy* 37(11) (2009), 4379-4390.
- [17] Fasugba M.A., Krein P.T., Cost benefits and vehicle-to-grid regulation services of unidirectional charging of electric vehicles, *Proc. IEEE Energy Conversion Congress and Exposition* (2011), 827-834.
- [18] Sortomme E., El-Sharkawi M.A., Optimal combined bidding of vehicle-to-grid ancillary services, *IEEE Trans. Smart Grid* 3(1) (2012), 70-79.
- [19] Beck L.J., V2G-101: A Text about Vehicle-to-Grid, the Technology which Enables a Future of Clean and Efficient Electric-powered Transportation, Leonard Beck (2009).

