



RETROSPECTIVE ANALYSIS OF TRAFFIC CONGESTION FOR A CASE STUDY AT THIRUMAZHISAI JUNCTION

KIRAN KUMAR.J¹

¹Assistant Professor, Department of Civil Engineering,
Saveetha School of Engineering, Saveetha Institute of Medical and Technical Sciences
Thandalam, Chennai

S. RIZWAN²

²Undergraduate student, Department of Civil Engineering,
Saveetha School of Engineering, Saveetha Institute of Medical and Technical Sciences
Thandalam, Chennai

Corresponding author: kirankumar.jagdish@gmail.com

Abstract: The blended movement conditions in underdeveloped nations like India on urban streets posture security issues. The high increment in the quantity of vehicles on the streets has caused a noteworthy social issue the loss of lives through mishaps. The horrifying human hopelessness and the appalling monetary misfortune caused by street mishaps requests for the consideration of the public and requires the need of the arrangement of the issue. A multidisciplinary approach is required in understanding the issue and giving the required arrangements. An activity build is concerned because many highlights of parkways influence the security of vehicles and other street clients. The mischance condition in India is not kidding a direct result of quick development of engine vehicles during recent years and the insufficiency of a significant number of the streets and lanes to adapt up to the movement. The blended activities conditions introduce on the streets in India aggravate the issue more. Along these lines, India has the qualification of driving the world in lethal street mishaps. It is seen from measurable information accessible, that India has a high casualty rate (around 47) in contrast with some of created nations (2 to 4) per 10,000 vehicles. Activity blockage in India should be given some uncommon concern. The dire undertaking is in this way, to justify the plan of streets, crossing points and the controls administering street clients. Notwithstanding this more prominent consideration, likewise should be given to the association of medical aid and improvement of surgical offices like injury focuses keeping in mind the end goal to have better offices for natives.

Keywords: Congestion, Fatality rate, Traffic, Vehicle, Public transport, Infrastructure.

1. Introduction

Most of the urban areas in Country like India are experiencing multi-faceted issues because of the quick urbanization and sudden augmentation in the private transport. Blockages on the urban streets are besetting vehicle store in India and impact the urban economies in various ways. Blockage might be characterized as overabundance interest for go over its supply. Truth be told, the motivation behind why governments are compelled to return to their arrangements like in Delhi for urban transport considering expanding interest of go with in restricted accessible administrations like open transports. The event of clog on the city streets keeps the development of movement and prompting the terrible increment in the trek delay. Developing new street or the enlarging of a current street is a brief alleviation to the blockage, yet in future point of view it basically empowers the development of the new vehicle through expanded level and it might likewise switch away the utilization of open transport. Building new street does not generally hold useful for assortment of budgetary, ecological and political reasons, in truth by acquainting more prominent

request of vehicle with travel easily and spare time it mixes blockage on that street too. Against the major issue of developing and existing clog issues in the Indian urban areas, savvy movement control and data strategies are required that can along these lines diminish the activity blockage and increment request of open transport

2. Traffic congestion

Movement blockage is a condition on transport arranges that happens as utilize increments, and is portrayed by slower speeds, longer excursion times, and expanded vehicular queuing. At the point when activity request is sufficiently extraordinary that the communication between vehicles moderates the speed of the movement stream, these outcomes in some clog. While blockage is plausibility for any method of transportation, this will concentrate on vehicle clog on open streets. As request approaches the limit of a street (or of the crossing points along the street), outrageous movement clog sets in. At the point when vehicles are completely ceased for timeframes, this is conversationally known as a car influx or movement growl up. Movement clog can prompt drivers getting to be plainly baffled and participating in street seethe. Numerically, clog is typically taken a gander at as the quantity of vehicles that go through

a point in a window of time, or a stream.
Blockage stream fits standards of liquid flow

2.1. Cause

Activity clog happens when a volume of movement or modular split produces interest for space more prominent than the accessible road limit; this point is normally named immersion. There are various particular conditions which cause or irritate clog; the greater part of them decrease the limit of a street at a given point or over a specific length, or increment the quantity of vehicles required for a given volume of individuals or products. About portion of U.S. movement clog is repeating, and is ascribed to sheer weight of activity; a large portion of the rest is credited to activity episodes, street work and climate events. Activity inquire about still can't completely anticipate under which conditions a "road turned parking lot" (rather than substantial, yet easily streaming movement) may all of a sudden happen. It has been discovered that individual occurrences, (for example, mischances or even a solitary auto braking vigorously in a formerly smooth stream) may cause gradually expanding influences (a falling disappointment) which at that point spread out and make a supported congested driving conditions when, something else, ordinary stream may have proceeded for quite a while longer

2.2. Accident analysis

Mishap investigation is done so as to decide the reason or reasons for a mischance (that can bring about single or numerous results) in order to forestall encourage mishaps of a comparative kind. It is a piece of mishap examination or episode examination. These investigations might be performed by a scope of specialists, including criminological researchers, scientific architects or wellbeing and security counselors. Mischance specialists, especially those in the air ship industry, are conversationally known as "tin-kickers". Health & Safety and patient wellbeing experts incline toward utilizing the expression "occurrence" set up of the expression "mishap". Its review nature implies that mishap investigation is basically an activity of coordinated clarification; led utilizing the hypotheses or techniques the investigator needs to hand, which coordinates the path in which the occasions, viewpoints, or highlights of mischance wonders are featured and clarified.

3. Literature Review

Takyi Harriet et.al (2013), collected the primary information using a victimization type instrument. Descriptive statistics was accustomed to analyze the data with the assistance of mathematics Package for

Social Sciences (SPSS). Increase in transport volume moreover as improvement among the traffic management and system got to run attention to spice up the installation among the metropolis. This would enhance worker productivity and ultimately increase gross domestic product

Mahmud Hassan Talukdar et.al (2013) studied on the traffic congestions and analyzed the several serious international issues in all nice cities resulted from fast urbanization that perpetually exert negative externalities upon society. The main aim of this study is to organize a hold up mitigation framework which can be helpful for urban planners, transport planners, civil engineers, transport policy manufacturers, congestion management researchers UN are directly concerned and are willing to involve within the task of hold up management. Review of literature is extensively carried out in this study and the global take on traffic congestion is outlined elaborately and the causes of hold up are concisely delineated. The causes were described keeping in mind the victimization all round the world.

Joseph. O. Ukpata1 et.al, (2012) investigates the transportation pattern by using questionnaires. The responses were recorded among participants comprising specialists in transportation designing and

style likewise as engineers of different disciplines, students, wives of engineers and different invited guests UN agency represent commuters, automobile owners/drivers, etc. 196 responses were collected and these were analyzed to determine the broad views regarding the causes of tie up in most urban cities in African nation. The results exhibited poor driving habits, poor road network, and inadequate road capability.

Lokoja et.al, (2013), examined the traffic delay downside and its causes at elect road intersections in Ilorin. Additionally, traffic volume and delay characteristics were calculable. Information was collected through direct field surveys on intersection characteristics, traffic volume, composition, delay causes and land use activities. The analysis of information collected unconcealed that variations exist in traffic flows and delays at the studied intersections. Also, traffic delays are discovered to be related to the traffic volumes at the assorted junctions that ultimately translate to tie up. In addition to the above data collected, traffic wardens and parking issues were found to be the major cause of delays at the road intersections within the town. The study recommends that the road intersections be signalized and vehicle parking be strictly prohibited to cut back tie up and delays at road intersections within the town.

Andrea Schrage et.al, (2006) compared the model while not accidents, wherever the toll equals external prices obligatory on drivers' mistreatment the road at a similar time, a replacement insight arises associate degree best toll conjointly internalizes the expected increase in future congestion prices. Accidents will cause an impact on drivers if traffic volumes are rising than after they are reducing, the efficient charge depends upon the demand for road use throughout the remainder of the height amount.

D Das et.al, (2015) conveyed that the traffic congestion could be a challenge resulting in undesirable consequences in most of the cities of the planet. Owing to its distinctive physical, spatial, road network, economic characteristics and demand of the quality of significant vehicles additionally to the traditional town traffic faces typical hold up challenges in its CBD space, significantly throughout the height hours, that secure this investigation. The study was conducted supported the critique of relevant literature to grasp the management variables influencing hold up, and examination of the relevance of relevant empirical models for assessing hold up and reengineering resolution, such as, traffic diversion from the engorged roads to the under-utilized or least engorged roads may assist in easing the hold up, increase in speed and reduction in period ensuing into optimum usage of all the roads.

Dr. Tripta Goyal et.al (2015), studied on the mixed traffic conditions in third world countries like India on urban roads pose safety problems. The accident condition in India is serious because of rapid growth of motor vehicles over the past few years and the inadequacy of many of the roads and streets to cope up with the traffic. to rationalize the look of roads, intersections and therefore the laws governing road users. In addition to this greater attention, also needs to be given to the organization of first aid and development of surgical facilities like trauma centers to have better facilities for citizens.

Yazan Issa (2014) studied on how individuals associate to the extent of congestion with significant traffic volumes, however it is not restricted solely to roadways, the most objectives of this analysis are to spot the doable congestion management techniques that are used round the world, and the software available to evaluate such techniques. The applicability and effectiveness of some of these techniques are then tested on available national and international data by comparing measures of effectiveness (capacity, LOS, delay, and speed) before and after applying these management measures. It was found that some congestion management measures

can be applied urban arterials, while others could not be applied easily.

Ankush Kumar et.al (2017) analyzed the complications and hazard on the cities roads due to increase rate of road users and traffic volume. Most of the cities in India are already suffering with huge deficiencies in term of infrastructures as well as in operational efficiencies. Considering the policy gaps on country roads this paper first describes the factor causing the congestion and after that presents some recommended measures to reduce the congestion on the city roads.

Vipin Jain et.al (2012), traffic jams still stay a serious downside in most cities round the world, particularly in developing regions leading to large delays. Our algorithmic rule is specifically designed for streaky traffic feeds with poor image quality. Based on live CCTV camera feeds from multiple traffic signals in Kenya and Brazil, we show evidence of this congestion collapse behavior lasting long time-periods across multiple locations. To partially alleviate this problem, we present a local de-congestion protocol that coordinates traffic signal behavior within a small area and can locally prevent congestion collapse sustaining time variant traffic bursts.

M. Absar Alam et.al (2013) studies the traffic in choose Asian cities and the policy measures undertaken by their individual governments. It revisits relevant policies in Asian nation and assesses the gaps that deter the required impact of such policies on reducing traffic jam. It conjointly suggests policy measures to beat these gaps and the means ahead.

S.B. Raheem, et.al (2015) coined that due to increase in population and therefore the attraction of human activities into urban region that successively ends up in the expansion of car possession and use, there's demand for road house that has light-emitting diode to extend within the range of conveyance operation. A case study has been analyzed victimization experimental and theoretical approaches. These involve traffic investigating and delay survey. to hold out effective analysis work on the case study road, the strategy adopted were traffic investigating and traffic delay survey.

Bee pin tey, et.al (1994) urban holdup square measure growing speedily and has become an ill-natured downside for many cities these days. this thesis can address the causes and consequences and varied ways that are curb it. It was found to be the world first road comprehensive road valuation system in effect. With age, the electronic road valuation application had become a lot

of easier these days the road system has become technically manageable possible.

Changzhi Bian, et.al (2016) analyzed the traffic using the net map information the long run reveals the potent that will impact them. First the \$64000 time hold up obtained from on-line map of auto-navy in a very fifteen-minute interval. Then, a replacement measurement index is introduced to explain the characterization of congestion patterns in every town supported on-line map information. Then external analysis is the cluster analysis based on the temporal distribution of the congestion that helps to spot the teams.

Awari Mahesh Babu, et.al (2016) found that there is an improvement in the whole nation development, surroundings and socio-economic customs developments. To boot the special blessings of the road transport individual are facing uncommon troubles attributable to the necessity of its appropriate organization, freshen up & preservation. With the bizarre difficulty of road transport, traffic delay and overcrowding are the rising troubles within the urban region. varied authentic issues and solutions of traffic delay and overcrowding are mentioned during this paper.

Nilanchal Patel, et.al (2015) Traffic congestion could be a major and growing downside in urban areas across the globe. It

reduces the effective abstraction interaction between completely different locations. To mitigate traffic jam, not solely the standing of various routes wants to be far-famed however conjointly it's imperative to see network congestion in numerous spatial zones related to distinct land use categories. Within the gift paper, a new formula is planned to quantify traffic jam within the completely different abstraction zones of a study space characterised by distinct land use categories. The planned formula is termed the Traffic Congestability Value (TCV). The formula considers three major influencing factors: congestion index price, pedestrian movement and road surface conditions; since these parameters area unit considerably associated with land use in an exceedingly region. the various traffic jam parameters, i.e. period, average speed and the proportion of your time stopped.

4. Conclusion

Traffic congestion may be an international yet as native downside. All round the globe, the prime reason behind tie up is on street parking. In Chennai, tie up may be a common issue like Mumbai. Completely different infrastructural and social control outcomes area unit granted for reducing tie up. By rearranging the signals and there timing it will make changes. Even by building a ring road at that junction it will

helps a lot and makes the traffic flow without any disturbance.

5. Reference

- [1] Broadstock. D. C. et al. (2011). Transportation oil demand, consumer preferences and asymmetric prices. *Journal of Education Studies*, vol. 38 No5 pp. 528-536.
- [2] Department of transportation, U.S. (2005), *Traffic congestion and reliability: Trends and advanced strategies for congestion mitigation* Office of Operations, Texas Transportation Institute, Federal Highway Administration.
- [3] Aderamo, A. J and Atomode. T.I. (2011), Traffic Congestion at Road Intersection in Ilorin, Nigeria. *Australian Journal of Basics and Applied Sciences*, 5 (9), 1439-1448.
- [4] Weiping, H., and Chi, W. (2010): Urban Road Network Accessibility Evaluation Method Based on GIS Spatial Analysis Techniques. *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, Vol. 38, Part II
- [5] Calthrop, E. and S. Proost (1998): *Road Transport Externalities*, *Environmental and Resource Economics* 11, 335–348.
- [6] Alterkawi, M.M. 2006. A computer simulation analysis for optimizing bus stops spacing: the case of Riyadh, Saudi Arabia, *Habitat International*, 30(3): 500-508.
- [7] Kadiyali, L.R. “Traffic Engg. And transport planning” Khanna Publishers, 1986 American Association of State Highway and Transportation Officials, AASHTO (2001). “A Policy on Geometric Design of Highways and Streets, Washington, D.C.”
- [8] P. Parvizi, S. Mohammdi, “Intelligent BRT in Tehran”, *World Academy of Science, Engineering and Technology*, pp. 1887-1890, 59 2011.
- [9] V. Jain, A. Sharma, A. Dhananjay, and L. Subramanian. Traffic density estimation for noisy camera sources. In *TRB 91st Annual Meeting*, Washington D. C., January 2012.
- [10] T. and S. Sundar (2013), Can We Reduce the Rate of Growth of Car Ownership? *Economic and Political Weekly*, Vol. 48, No. 23, pp. 32-40.
- [11] Filani, M.O. and Olateru - Olagbegi S.A. (1976): *Urban Transportation in*

relation to land use in Nigeria. Paper presented at NISER Conference on the land policy in Nigeria, Ibadan.

[12] "Singapore road pricing system 1975-1989", Singapore: centre for transportation studies, NTU,1992.

[13] Manawa Anakpa, Yuyu Yuan, and Ghazaros Barseghyan Research Article (8 pages), Article ID 5636319, Volume 2018 (2018).

[14] Y. and Tsukaguchi H., 2005: Relationships between Network Topology and Pedestrian Route Choice Behavior. In: Journal of the Eastern Asia Society for Transportation Studies, Vol. 6, pp. 241-248.

