

DESIGN AND FABRICATION OF AUTOMATION WHEEL ASSEMBLY SYSTEM

¹Jai Rajesh.P, ²Mohanakumaresan.B

¹Assistant Professor, Department of Mechatronics Engineering, BIST, BIHER, Bharath University, Chennai-73

²Student, Department of Mechatronics Engineering, BIST, BIHER, Bharath University, Chennai-73

¹jairajesh.mechatronics@bharathuniv.ac.inUG

Abstract: This Real framework is hard to deal with, set up to Assess the execution of a wheel stacking framework, the recreation bundle ought to be accessible to gauge the execution of the framework with a picked robot. The mechanized wheel gathering framework lessens human exertion time, vitality. The continuous work is finished with the robot precisely. Here the camera is supplanted by the IR sensor which the cost is radically lessened and measures up to a similar work.

Keywords: assembly robots; software : Plc ,Proe.

1. Introduction

In this car fabricating wheel stacking is the procedure to mount the wheels onto an auto when the generation line is moving indiscriminately speed. At present this process is finished by the administrators w/o helped gadgets as appeared in Figure.

There are normally 6 administrators for every move in each generation line and two moves every day for wheel stacking.

Consequently, the cost for wheel stacking is around 1.5 million dollars every year for a mechanical production system in view of the current cost of an operator (about \$130K every year in the United States). The request to robotize the wheel stacking process is getting increasingly elevated, particularly when the car producing is confronting troublesome time [1,2]. There are many difficulties to robotize the wheel stacking process. At the point when the auto is proceeding onward the generation line, it could move along both the X and Y bearings indiscriminately speed as appeared in Figure 2. In this manner, the computerized wheel stacking framework ought to have the capacity to track the arbitrary movement. Of the auto precisely since the get together resistance of wheel stacking is very little [3,4]. Likewise wheel stacking is near the last stride of the entire auto get together and the auto is nearly prepared to go. Along these lines, a little harm to the auto could cause a enormous misfortune. Accordingly, the created

robot framework must be consistent to the movement of the auto once the wheel contacts the auto. Modern robots have expanded in both number and many-sided quality throughout the years for get together assignments since adaptability and the expanding necessities of item quality and amount [5,6]. Be that



Figure1. Manual assembly by human and is increasing the time and human effort and energy also.

As it may, get together robots are as yet a little part of aggregate robot deals every year. One of the fundamental reasons is that it is troublesome for regular mechanical robots to change in accordance with any kind of change of the get together procedures [6]. Along these lines, more Be that as it may, just a single bearing movement (X hub in Figure 2) is followed and the wheel center must be all around adjusted in the heading of the movement of the transport. In any case, the wheel center point can't be precisely adjusted at a similar heading for all autos on the creation line. Yoon [2] utilized stereo vision to distinguish the wheel center point position and introduction while the creation line is moving. Be that as it may, the posture estimation mistakes are more than 3mm that is more than the wheel stacking resilience. In this way the created framework is most certainly not prepared for use in the genuine wheel stacking process. Additionally, these frameworks utilize just visual servoing to track the movement of the auto to play out the get together undertakings. In wheel stacking, the

glitch of the visual servoing could harm the auto body, which is exorbitant[7,8]. To make the automated framework consistent with the contact condition, constrain control can be utilized. Thusly, to empower wheel stacking, visual servoing and constrain control must be coordinated to control the movement of the automated framework. Beaten et al. built up a cross breed vision and constrain control procedure to take after the form of planar surface. In spite of the fact that these strategies can manage the highlight following in view of half and half control system, the applications in the moving item following while playing out specific assignments are not talked about[9,10]. Nelson et al. talked about various techniques in view of vision and constrain control, for example, half breed control, exchanged control and shared control strategies. Fascinating test comes about are displayed with respect to the execution of these techniques. Nonetheless, the compel control is just used to keep up a certain contact constrain. In spite of the fact that blend of vision and constrain control system has been broadly examined, no down to earth usage in wheel stacking has been done in view of the synergistic blend of vision, constrain and position as the criticism data. Canny modern mechanical frameworks must be created keeping in mind the end goal to perform complex get together assignments like wheel stacking[11]. There are some examination papers about wheel stacking. Cho built up a wheel stacking framework in view of visual servoing. Since the wheel stacking resistance is very little, a large scale smaller scale controller control technique is produced to increment the framework data transfer capacity and following precision. Since the stereo vision framework requires high caliber camera, precise adjustments and high calculation control, the current frameworks are expensive, mistake inclined and not strong enough for every day use at the workshop[12]. Likewise the confused calculation for deciding the position/introduction of an object makes the framework hard to be executed in genuine time applications. Moreover, the visual servoing alone could make harms the last items if the vision framework is failed. Henceforth a straightforward IR framework joined with compel control is a superior answer for modern applications.

To play out a get together utilizing an IR sensors framework, the blunders along the X-and Y-tomahawks of the moving part can be remunerated by flag servoing, nonetheless, the Z pivot mistakes are hard to remunerate utilizing IR. Thus, constrain control can be connected to control the movement of a mechanical framework to play out a gathering assignment along the Z axis. Here, it talks about a gathering innovation for wheel stacking while the auto is moving in light of flag servoing also, compel

control. The wheel stacking framework had been set up and tries were performed effectively[13,14].

The trial comes about exhibit that the created innovation can likewise be utilized for gathering while the part on thesequential construction system is moving haphazardly.

1.1 Wheel Loading Process

The wheel stacking process is to mount the wheel onto the wheel center point on the auto as appeared in Figure 3. The gaps the wheel center mount the wheel onto the wheel center point to coordinate the studs on the wheel center so as to





Figure 2

2. Mount the Wheel onto the hub page

Design Figure 4 demonstrates a wheel stacking framework. The wheel stacking station incorporates a robot with sensors, robot controller and transport that the auto is settled on and so forth. An ABB IRB6600 robot with an extra hub (Axis 7) is controlled to consequently mount the wheel onto a wheel center while it is haphazardly moving[15]. Since the wheel is arbitrarily stacked into the station, the wheel area counting position and introduction must be recognized utilizing the vision framework. On the off chance that the wheel is discovered, the wheel is gotten by the robot gripper and the robot moves to the beginning position

sitting tight for the auto. On the off chance that the auto is distinguished by a magnet switch mounted on the transport, the vision framework distinguishes the area including the position and introduction of the wheel center[16]. The wheel is then turned by Pivot 7 to coordinate the introduction of the wheel center point.



The robot at that point begins to track the movement of the auto while the wheel mounting is performed. On the off chance that the procedure is effective, the gripper is open and the wheel is mounted on the wheel center. The robot instrument is then withdrawn[17,18]. On the off chance that the process comes up short, the robot instrument with the wheel is withdrawn. Manual wheel stacking must be performed to settle the issue. The general plan is made in various programming to discover the exactness of the plan and the straightforward outline is done in rapidly spreading fire ace e This

straightforward model gives the general articulation of the mechanical get together framework

1. The IR sensor recognizes the position/introduction of a haggle it up

2. The robot moves to the beginning position (instructed physically).

The IR sensor will give the information to the transport triggers

The primary trigger. After picture handling, the introduction

example of the jolts on the center is recognized. The robot Axis 7 will turn to coordinate the gaps on the wheel to the studs on the wheel center.



(a) Wheel is picked by a robot continuously.



(b) Wheel is assembled by a robot continuously.

3. While Axis 7 is turning, the robot moves to the second Position. At the point when the second trigger is activated,

the vision framework will recognize the speed of the auto furthermore, track it. In the meantime, drive control is empowered along all headings. The robot will move towards the center in light of drive control along Z-hub

4. Once the contact constrain along Z-pivot achieves the set esteem and the apparatus position along the gathering bearing achieves the set esteem, the gathering finishes and the constrain control along the negative Zaxis will withdraw the robot.

5. The constrain control along all headings will keep the framework safe under anomalous conditions. For instance, at the point when the vision framework sends

wrong flags, the drive control will adjust the wrong flags and won't make harm the framework and the item.

2.1 Control System Structure

The created wheel stacking framework can track the moving auto body while mounting the wheel onto the wheel center point in view of the vision, compel and position sensor combination. The movement of the transport is commonly irregular with the speed change along both the X and Y bearings. Subsequently the robot needs to track the movement of the moving part along both the X and Y bearings keeping in mind the end goal to play out the get together procedures. This is unique in relation to the run of the mill transport following procedure which just the movement along the X heading is controlled[19,20]. Since the framework includes the vision framework, constrain control framework and the robot control framework, the control framework structure is examined first.

A simple approach to finish y with the gathering paper designing necessities is to utilize this archive as a format and basically sort your content into it. Since the framework includes the vision framework, constrain control framework and the robot control framework, the control framework structure is examined first PLC controller.

The control framework equipment setup is appeared in Figure 8. The IR sensor framework forms the signs and sends the[18] position signs to the robot controller (IRC5, an ABB controller) to control the movement of the robot to take after the movement of the protest. The drive sensor measures the contact compel to modify the movement of the robot. The compel control additionally makes the robot agreeable to the earth to evade the harm to the contact protest. In the IR framework, a pre-characterized highlight on the moving [19] part is recognized by a spared signals. The position blunder of the element contrasted and the coveted component in the casing is figured to control the movement of the robot as appeared in, the robot can just track the movement of the moving part along the X and Y headings. To play out a gathering, the robot must be controlled to approach the moving part. Consequently, compel control along the Z pivot is connected to control the movement of the robot to play out the wheel stacking process. Since the infrared servoing alone could make harms the last items if the IR framework is broke down, the drive control along both the X and Y to makes are additionally empowered to make the automated framework consistent to the contact condition. There are a few arrange outlines engaged with the[27]


2.2 Framework:

The transport outline (work question outline), the include outline, the camera outline, the device outline (gripper), the constrain sensor outline,[28] the robot base edge and the world outline. The vast majority of the casings are basic aside from the element outline. The component outline is characterized on the focal point of the include and is parallel to the work protest outline.

2.3 Savvy control system

Since the wheel stacking process needs human information, a canny automated framework is created to play out the confused get together process.[29] The insightful mechanical framework utilizes the accompanying guidelines. On the off chance that the component is distinguished, at that point the robot begins to track the moving auto[21]. The element is characterized by the client, either a genuine highlight on the auto or an additional component. The movement controller is empowered to control the gathering procedure after the element is distinguished. In the event that the contact constrain between the robot instrument and the moving auto achieves a set esteem and the apparatus position comes to a set an incentive along the get together bearing (Z hub) then the get together process is finished and the robot device is withdrawn. Since the protest is moving haphazardly, the area of the culmination point is distinctive at every get together. At the point when the contact drive is too enormous, there might be a stick between the robot and the moving item. Since both themechanical framework[23] and the moving auto on the generation line are very hardened, they must be separate quickly to maintain a strategic distance from harm[12,18]. In this manner, speedy withdraw is required. In the event that the robot apparatus approaches the get together contact point along the get together heading, the control coefficients ought to be exchanged.[24] The contact point is diverse at each get together. Before the robot apparatus achieves the point, the visual servoing control overwhelms the control circle since the following precision is imperative. Once the robot device contacts the moving item, the robot ought to be consistent to the condition to dodge harm of the automated framework and the moving auto. In this way, the constrain control ought to overwhelm the control circle. These guidelines are imperative to make the get together process fruitful. Since the auto is moving haphazardly, the get together fruition point and the contact point and so on can't be prearranged. Along these lines, the created clever framework can bargain with the change of the workplace. [26]

The movement of the robot is controlled by the robot controller in view of the vision and constrain sensor inputs. The control framework structure



3. Trial Implementation and Results

To approve the created strategy, tests were actualized to play out the wheel stacking process while the auto is proceeding onward a mechanical production system.[31] There are a few adjustments associated with the wheel stacking process. To begin with, the gaps on the haggles on the wheel center point have to be coordinated. This is finished by instructing the device introduction. While moving the robot instrument around the include, the change between the instrument outline, the include outline and the camera outline is then processed. The change between the haggles outline is aligned by moving the camera to a few extraordinary positions while the pictures are caught. [32]The distance across of the stud's tip on the wheel center point is about 16mm and that of the gap on the wheel is around 20mm. Consequently the resistance of the get together is around 2mm from the focal point of the opening. Since the wheel center point is moving. Arbitrarily with the auto on the transport, the following blunder must be under 2mm to introduce the wheel onto the wheel center point effectively[33].

4. Conclusions

Since most current modern robots must be prearranged with next to no adjustment in their assignment execution, they are hard to fulfill the expanding complex assembling prerequisites, for example, wheel stacking. In this paper, a robotized wheel stacking framework is produced in light of the synergistic mix of visual servoing and constrain control technique. Visual servoing is utilized to track the 2D movement of the auto on the transport. Examinations were performed effectively and the outcomes shown that the created innovation can be utilized for wheel stacking. Since enormous measure of time and asset can be spared utilizing the created mechanical framework, this inventive innovation will

have extraordinary effect in the car industry, particularly when car producing is confronting troubles.

References

- [1] C. Cho, S. Kang, M. Kim, and J. Song, "Macro-Micro Manipulation with Visual Tracking and its Application to Wheel Assembly", The
- [2] International Journal of Control, Automation, and Systems, vol. 3, no. 3, pp. 461-468, September 2005
- [3] Ganeshram V., Achudhan M., Synthesis and characterization of phenol formaldehyde resin as a binder used for coated abrasives, Indian Journal of Science and Technology, v-6, i-SUPPL.6, pp-4814-4823, 2013.
- [4] Achudhan M., Prem Jayakumar M., Mathematical modeling and control of an electrically-heated catalyst, International Journal of Applied Engineering Research, v-9, i-23, pp-23013-, 2014.
- [5] Anbazhagan R., Satheesh B., Gopalakrishnan K., Mathematical modeling and simulation of modern cars in the role of stability analysis, Indian Journal of Science and Technology, v-6, i-SUPPL5, pp-4633-4641, 2013.
- [6] Udayakumar R., Kaliyamurthi K.P., Khanaa, Thooyamani K.P., Data mining a boon: Predictive system for university topper women in academia, World Applied Sciences Journal, v-29, i-14, pp-86-90, 2014.
- [7] Kaliyamurthi K.P., Parameswari D., Udayakumar R., QOS aware privacy preserving location monitoring in wireless sensor network, Indian Journal of Science and Technology, v-6, i-SUPPL5, pp-4648-4652, 2013.
- [8] Youngrock Yoon DeSouza, G.N. Kak, A.C., "Real-time tracking and pose estimation for industrial objects using geometric features", IEEE International Conference on Robotics and Automation, pp3473-3478, Sept. 2003.
- [9] Venkatesan N., Srinivasan V., Fabrication and mechanical properties of natural composite materials, International Journal of Applied Engineering Research, v-9, i-22, pp-7743-7748, 2014.
- [10] Mustafa Kamal Basha M., Srinivasan V., Fabrication of AlSiC Mmc and analysis of its mechanical properties, International Journal of Applied Engineering Research, v-9, i-22, pp-7621-7626, 2014.
- [11] Selvam M.D., Srinivasan V., Sekar C.B., An attempt to minimize lubricants in various metal cutting processes, International Journal of Applied Engineering Research, v-9, i-22, pp-7688-7692, 2014.
- [12] J. Baeten and J. D. Schutter, "Hybrid vision/force control at corners in planar robotic-contour following," IEEE/ASME Transactions on
- [13] Mechatronics, vol. 7, no. 2, pp. 143 – 151, June 2002.
- [14] Srinivasan V., Optimizing air traffic conflict and congestion using genetic algorithm, Middle - East Journal of Scientific Research, v-20, i-4, pp-456-461, 2014.

- [15] Praveen R., Achudhan M., Optimization of jute composite as a noise retardant material, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7627-7632, 2014.
- [16] J. Baeten, H. Bruyninckx, and J. D. Schutter, "Tool/camera configurations for eye-in-hand hybrid vision/force control," in *IEEE*
- [17] *International Conference on Robotics and Automation*, Washington, DC, pp. 1704-1709, May 2002
- [18] Prem Jeya Kumar M., Gopalakrishnan K., Srinivasan V., Anbazhagan R., Sundeep Aanan J., PC modeling and simulation of car suspension system, *Indian Journal of Science and Technology*, v-6, i-SUPPL5, pp-4629-4632, 2013.
- [19] Jeykar K., Srinivasan V., Performance characteristics of twin cylinder Di diesel engine operated with three different non edible vegetable oil blends with diesel, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7601-7607, 2014.
- [20] Srinivasan K., Gopikrishnan M., Analysis of a reduced switch three phase BLDC drive, *International Journal of Applied Engineering Research*, v-9, i-22, pp-6633-6637, 2014.
- [21] D. Xiao, B. K. Ghosh, N. Xi, and T. J. Tarn, "Sensor-based hybrid position/force control of a robot manipulator in an uncelebrated environment," *IEEE Transactions On Control Systems Technology*, vol. 8, no. 4, pp. 635-645, July 2000.
- [22] Gopalakrishnan K., Prem Jeya Kumar M., Sundeep Aanan J., Udayakumar R., Analysis of static and dynamic load on hydrostatic bearing with variable viscosity and pressure, *Indian Journal of Science and Technology*, v-6, i-SUPPL.6, pp-4783-4788, 2013.
- [23] Prem Jeya Kumar M., Sandeep Anand J., Gopalakrishnan K., Satheesh B., Anbazhagan R., Computer modelling of a vehicle system, *Indian Journal of Science and Technology*, v-6, i-SUPPL5, pp-4620-4628, 2013.
- [24] Prem Jeya Kumar M., Gopalakrishnan K., Srinivasan V., Anbazhagan R., Sundeep Aanan J., PC modeling and simulation of car suspension system, *Indian Journal of Science and Technology*, v-6, i-SUPPL5, pp-4629-4632, 2013.
- [25] Jeykar K., Srinivasan V., Performance characteristics of twin cylinder Di diesel engine operated with three different non edible vegetable oil blends with diesel, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7601-7607, 2014.
- [26] Srinivasan K., Gopikrishnan M., Analysis of a reduced switch three phase BLDC drive, *International Journal of Applied Engineering Research*, v-9, i-22, pp-6633-6637, 2014.] Venkatesan N., Srinivasan V., Fabrication and mechanical properties of natural composite materials, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7743-7748, 2014.
- [27] Mustafa Kamal Basha M., Srinivasan V., Fabrication of AlSiC Mmc and analysis of its mechanical properties, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7621-7626, 2014.
- [28] Selvam M.D., Srinivasan V., Sekar C.B., An attempt to minimize lubricants in various metal cutting processes, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7688-7692, 2014.
- [29] Arun Kumar N., Srinivasan V., Krishna Kumar P., Analysing the strength of unidirectional fibre orientations under transverse static load, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7749-7754, 2014.
- [30] Srinivasan V., Analysis of static and dynamic load on hydrostatic bearing with variable viscosity and pressure, *Indian Journal of Science and Technology*, v-6, i-SUPPL.6, pp-4777-4782, 2013.
- [31] Srinivasan V., Optimizing air traffic conflict and congestion using genetic algorithm, *Middle - East Journal of Scientific Research*, v-20, i-4, pp-456-461, 2014.
- [32] Praveen R., Achudhan M., Optimization of jute composite as a noise retardant material, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7627-7632, 2014.
- [33] Raja Kumar G., Achudhan M., Srinivasa Rao G., Studies on corrosion behaviour of borated stainless steel (304B) welds, *International Journal of Applied Engineering Research*, v-9, i-22, pp-7767-7772, 2014.
- [34] Ganeshram V., Achudhan M., Design and moldflow analysis of piston cooling nozzle in automobiles, *Indian Journal of Science and Technology*, v-6, i-SUPPL.6, pp-4808-4813, 2013.
- [35] Ganeshram V., Achudhan M., Synthesis and characterization of phenol formaldehyde resin as a binder used for coated abrasives, *Indian Journal of Science and Technology*, v-6, i-SUPPL.6, pp-4814-4823, 2013.
- [36] Achudhan M., Prem Jayakumar M., Mathematical modeling and control of an electrically-heated catalyst, *International Journal of Applied Engineering Research*, v-9, i-23, pp-23013-, 2014.
- [37] Anbazhagan R., Satheesh B., Gopalakrishnan K., Mathematical modeling and simulation of modern cars in the role of stability analysis, *Indian Journal of Science and Technology*, v-6, i-SUPPL5, pp-4633-4641, 2013.
- [38] Udayakumar R., Kaliyamurthie K.P., Khanaa, Thooyamani K.P., Data mining a boon: Predictive system for university topper women in academia, *World Applied Sciences Journal*, v-29, i-14, pp-86-90, 2014.
- [39] Kaliyamurthie K.P., Parameswari D., Udayakumar R., QOS aware privacy preserving location monitoring in wireless sensor network, *Indian Journal of Science and Technology*, v-6, i-SUPPL5, pp-4648-4652, 2013.

