

MEDICAL IMAGING TECHNIQUE TO DETECT TUMOR CELLS

¹Sivaranjani S, ²Kaarthik K,

^{1,2}Assistant Professor, Department of Electronics and Communication Engineering,

^{1,2}M.Kumarasamy College of Engineering (Autonomous),

Thalavapalayam, Karur, Tamilnadu, India

¹ssivaranjani.ece@mkce.ac.in, ²kaarthikk.ece@mkce.ac.in

Abstract: Boundary is exploiting to make a distinction two dissimilar regions in image processing technique. Boundary endow with transparency to human eye in understanding any observation. It plays a major role in medical field, as finding the right limit in uproarious images is as yet a troublesome assignment. Here we introduce the new technique of detection using the information of intensity and texture of an image. The proposed technique spots the uproarious images in the object boundaries using the data from the intensity gradient by means of the vector picture show and the surface slope by means of the edge delineate. The proposed technique on various medical images using Self organizing map (SOM) clustering provides correct boundaries even in an ill-defined images and multi grey level images. This technique is strong and relevant on different sorts of uproarious pictures without earlier information of noise properties.

Keywords: Extraction in Boundary; Edge Following; SOM Clustering

1. Introduction

This Image Segmentation is an underlying advance before performing abnormal state assignments. While considering the instance of a brain tumor tolerant, the MRI output of his cerebrum demonstrates the tumor yet not unmistakably. On the off chance that the boundaries of tumor are identified then its size can be computed and promote drug can be arranged. So with a specific end goal to discover the boundary we have to comprehend the essential picture handling step i.e., Segmentation. Segmentation segments an input image into its constituent parts or questions[11]. Output of segmentation is typically crude pixel information constituting either boundary of an area or all focuses in that locale. Segmentation algorithms are generally based on two properties of grey level values, discontinuity and

similarity. Initial one depends on sudden changes in grey levels for the most part recognizes lines and edges. Second one depends on thresholding, region splitting and merging. Such huge numbers of edge based calculations as Sobel, Prewitt, Laplacian and locale based methodologies as area developing, consolidating, grouping have been executed. However the execution evaluation of Image segmentation comes about is as yet a testing issue as they fail to extract the correct boundaries of objects in noisy images.

Boundary can be identified in an uproarious picture by the previously mentioned calculations however a large portion of the calculations experience issues in identifying boundary in pictures with badly characterized edges. In numerous medicinal pictures like in checked pictures of lungs and mind, the aggregations of organs with blockages or harms can't be made sense of accurately as they are excessively perplexing and loud. As a solution for this issue, we propose the strategy of edge following technique in view of the power and surface estimations of the picture. Power alludes to the splendor of a point in a picture and is controlled by a few amounts including the neighborhood focus, the quantum proficiency of the fluorophore, and affectability of the light sensor in the imaging framework. Surface gives us data about the spatial game plan of shading or powers in a picture or chose district of a picture and this is one way that can be utilized for segmentation [11]. The force slope is characterized as the directional change in the shading estimation of a picture. Since the force capacity of an advanced picture is just known at discrete focuses, subordinate of this capacity is considered as a rule. A total depiction of a picture we consider the two headings and extents of picture edges as vector picture demonstrate. The vector picture display, a subsidiary based edge administrator [4] is connected to get the edge vector field which is gotten by averaging sizes and bearings in the vector picture. Number of strategies [2] has been proposed,

One of the best methods is edge delineate is gotten from law's surface and the vigilant edge recognition. The vector picture model and edge delineate connected to choose the best edges. The procedure of boundary location did utilizing force angle and surface slope is helpful and gives great outcomes if the picture has least scope of dim esteems. On the off chance that more varieties in dim esteems is found in a picture then it will be tedious. Also the estimations of need to bolstered physically for each picture which makes it additional tedious, thus a programmed strategy is required. Self-Organizing map (SOM) plays an important role in clustering. Its attractive features are input space approximation, topological ordering and density matching helps in simple implementation of boundary detection. The paper is organized as follows. Section II and III describes the boundary detection using vector image model and edge map and -organizing map clustering method for boundary detection. Section IV describes the self and compare the results with edge based method. Section V concludes the paper.

2. Boundary Detection Algorithm

The proposed algorithm consists of four phases.




Figure 1. Block diagram of the proposed method

The Proposed technique has experienced a few stages to distinguish the Tumor cells. The means are as per the following:

Step 1: In our proposed method we consider the MRI scan of brain tumor image is consider as

In put image the tumor but not clearly.

Step 2: The local features of an input image are extracted for further processing.

Step 3: Histogram features of an image is consider as a local features.

Step 4: Self-organizing map is applied in on the local features of an image for clustering operation.

Step 5: The boundary of the tumor is detected from the clustered data.

3. SOM Clustering

The boundary of tumor isn't recognized utilizing force angle and surface inclination strategy appeared in Fig. 3 So to get the boundary of the tumor, we continue with SOM grouping. In SOM the bunching is completed utilizing a two level approach, where picture is to begin with bunched utilizing SOM [15, 13] and afterward, the SOM is grouped. At to begin with, nearby highlights of restorative picture pixels are extricated to sustain a self-sorting out guide (SOM) after a preprocessing step. The yield models of SOM are then sifted with a hits outline a grouping strategy is connected to the models. Contrasted with Davies-Bolden (DB) grouping list and entropy picture division list, a quantitative picture assessment list is finally chosen for a best division. The division comes about after the post processing demonstrate the proposed technique to be compelling furthermore, encouraging [7,8].The run of the mill highlights of SOM are topology perception of the info designs and portrayal of countless examples with few models. The most vital quality of SOM is that the info designs which are comparable in the info space are additionally near each other topologically in the yield space. The Self-Organizing Feature Map gives a conservative portrayal of the information, has been generally connected in the perception of high-dimensional information.

In [6, 15] SOFM is an unsupervised learning system which holds rule 'highlights' of the info information. In SOFM topological structure forced on the hubs which jam neighborhood subtle elements has been introduced in [6, 15].A self-sorting out guide structure comprises of parts called outline or neurons. A single guide hub contains a weight vector pseudo- Zernike minutes have better highlights portrayal capacities. These minutes are invariant under picture turn, multilevel snapshots of a picture are utilized weight vector which have better highlights portrayal capacities. The course of action of hubs is a rectangular lattice. Guide hubs are not associated with each other but rather all the hubs are associated with each information hub. Self-organizing maps (SOMs) are a data visualization technique invented by Professor Teuvo Kohonen which reduces the dimensions of data through the use of self-organizing neural networks. In this configuration, each map node has a unique coordinate. This makes it easy to reference a node in the network, and to calculate the distances between nodes. Because of the connections only to the input nodes, the map nodes are oblivious as to what

values their neighbors Input Image Local Features Extraction SOM Training Tumor Boundary Detected have [12, 9]. A map node will only update its' weights based on what the input vector tells it. Each weight vector has two components. The first part of a weight vector is its data. This is of the same dimensions as the sample vectors and the second part of a weight vector [9, 14] is its natural location is the position of the pixel of the image.

The SOM Steps:

- M dimensional input $I = [I_1, I_2, I_3, \dots, I_n]$
- Each node's weights are initialized.
 $W_j = [w_1, w_2, w_3, \dots, w_m]$
- A texture feature vector (histogram) is presented to the network as a weight vector.
- Every node in the network is examined to calculate Best Matching Unit (BMU). The node with a weight vector closest to the input vector is tagged as winning node which done with the help of Euclidian distance between input and weight vector.
- The radius of the neighborhood of the best matching unit is calculated.
 $\sigma(t) = \sigma_0 e^{-t/\lambda}$
- Each neighboring nodes are adjusted with new weight to make them more toward the input vector. New weight of the node.
 $W(t+1) = W(t) + L_0 e^{-t/\lambda} h(t) \frac{0^2/2}{\sigma^2(t)} (I(t) - W(t))$
 $h(t) = e^{-(\text{distance from BMU})}$
- The above procedure is reshaped for each information vector for a number of cycles. The system ends up associating output nodes with bunches in the info informational data set.




Figure 2. Brain MR Image



Figure 3. Boundary of brain is detected but not the tumor.



Figure 4. Original image with tumor




Figure 5. Tumor being highlighted by its boundary



Figure 6. Original image



Figure 7. The boundary is detected by the proposed technique




Figure 8. Brain MR image with tumor



Figure 9. Tumor being extracted by its boundary detection

4. Experimental Results

The performances of the proposed technique have been tested by considering many medical images of brain. Some of the images are too noisy and some with ill-defined edges, But still the boundaries were detected by using the proposed method. The proposed technique results are shown in below figure

5. Conclusion

In this paper, SOM clustering methods are combined to realize the segmentation of medical images. Local features of mean and standard variance of pixels are preferred to be educated in SOM. Output prototypes are filtered by a hits map. The best cluster number can found under the directional Final segmentation result is acquired for brain MR images demonstrate that the proposed technique is viable and promising for detecting the tumor efficiently.

References

- [1] Maulik U, Bandyopadhyay S. Fuzzy partitioning using a real coded variable length genetic algorithm for pixel classification. *IEEE Trans Geosci Remote Sens* 2003;41(5):1075–81.
- [2] Wu S, Liew AWC, Yan H. Cluster analysis of gene expression data based on self-splitting and merging competitive learning. *IEEE Trans Inform Technol Biomed* 2004;8:5–15.
- [3] Zhu L, Chung FL, Wang S. Generalized fuzzy C-means clustering algorithm with improved fuzzy partitions. *IEEE Trans Syst Man Cybernet: Part B* 2009;39(3):578–91.
- [4] J. Eggermont, “Rule-Extraction and Learning in the BPSOM Architecture,” Leiden University, Internal Report IR-98-16 (Masters Thesis), August 1998.
- [5] J. Guerrero, S. E. Salcudean, J. A. McEwen, B. A. Masri, and S. Nicolaou, “Real-time vessel segmentation and tracking for ultrasound imaging applications,” *IEEE Trans. Med. Imag.*, vol. 26, no. 8, pp. 1079–1090, Aug. 2007.
- [6] K. Laws, “Textured image segmentation,” Ph.D. dissertation, Dept. Elec. Eng., Univ. Southern California, Los Angeles, 1980.
- [7] S. Palanivel Rajan, “Diagnosis of Cardiovascular Diseases using Retinal Images through Vessel Segmentation Graph”, *Current Medical Imaging Reviews*, Vol. : 13, 2017.
- [8] Pentland, R. W. Picard and S. Sclaroff, “Photobook content-based manipulation of image database,” *Journal of Computer Vision*, vol. 18(3), pp. 233–254, 1996
- [9] C. Yixin, J. Z. Wang, and R. Krovetz, “CLUE: Clusterbased retrieval of images by unsupervised learning,” *IEEE Trans. Image Process.*, vol. 14, no. 8, pp. 1187–1201, Aug. 2005
- [10] Pentland A., Picard R., and Sclaroff S. (1994), Photobook: Tools for content-based manipulation of image databases, In *Proceedings of the SPIE Conference on Storage and Retrieval for Image and Video Database II*, pp. 34–47.
- [11] Maulik, U. Medical image segmentation using genetic algorithms. *IEEE Transactions on Information Technology in Biomedicine* 2009; 13: 166 – 173.

- [12] M. Anitha, K. Kaarthik, Analysis of nutrient requirement of crops using its leaf, *Journal of Chemical and Pharmaceutical Sciences*, ISSN No.: 0974-2115, Special Issue 8, December 2016, PP.99 – 103.
- [13] Allen, A., Richey, et.al.(1991)Sex Differencesin The Corpus Callosum of The Living Human Being. *Journal of Neuroscience*, 11(4), pp933-942.
- [14] Muthusamy Madheswaran,Muthusamy Suganthi,“An Improved Medical Decision Support System to Identify the Breast Cancer Using Mammogram”. *J. Med. Syst.*(2010)
- [15] Yuvarani P and Maheswari S 2016, ‘Investigations of Various filters for lung Cancer CT Images’, *Journal of Chemical and Pharmaceutical Sciences*, Special Issue 8, Pages 79-81.
- [16] Yuvarani P 2012, ‘Image Denoising and Enhancement for Lung Cancer Detection Using Soft Computing Technique’ *IET Chennai 3rd International on Sustainable Energy and Intelligent Systems (SEISCON 2012)* IEEE Digital Library, Online ISBN: 978-1-84919-797-7DOI: 10.1049/cp.2012.2179 , Publisher.IET.
- [17] P.R.Gomathi, V.Jamuna,” Application of Independent Component Analysis”, *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering*, ISSN (Online): 2278–8875, Vol.3, special Issue 3, pp. 126-131, 2016.
- [18] S.Palanivel Rajan, et.al., “Visual and tag-based social image search based on hypergraph ranking method”, *IEEE Digital Library Xplore*, ISBN : 978-1-4799-3835-3, INSPEC Accession Number : 14916051, DOI : 10.1109/ICICES.2014.7034079, 2015.
- [19] Fahmi, R., El-Baz, A. et.al.Classification Techniques for Autistic vs.Typically Developing Brain using MRI DataProc. 4th IEEE.nternational Symposium on Biomedical Imaging: From Nano to Macro,pp1348-1351.
- [20] C.Vivek, S.Autdithan, Robust Analysis of the Rock Texture Image Based on the Boosting Classifier with Gabor Wavelet Features, *Journal of Theoretical and Applied Information Technology*, 2014, PP 562- 570 Vol. 69, Issue 3.
- [21] Hung, M.C. and D.L. yang, 2001. “An Efficient Fuzzy C meansClustering Algorithm”, *Data mining, ICDM 2001, Proceedings IEEE international conference* on pp: 225- 232
- [22] H. Greenspan and A. T. Pinhas, “Medical image categorization and retrieval for PACSusing theGMMKLframework,” *IEEE Trans. Inf. Techol. Biomed.*, vol. 11, no. 2, pp. 190–202, Mar. 2007.
- [23] T. Padmapriya and V.Saminadan, “Handoff Decision for Multi-user Multiclass Traffic in MIMO-LTE-A Networks”, *2nd International Conference on Intelligent Computing, Communication & Convergence (ICCC-2016) – Elsevier - PROCEEDIA OF COMPUTER SCIENCE*, vol. 92, pp: 410-417, August 2016.
- [24] S.V.Manikanthan and K.Baskaran “Low Cost VLSI Design Implementation of Sorting Network for ACSFD in Wireless Sensor Network”, *CiiT International Journal of Programmable Device Circuits and Systems*,Print: ISSN 0974 – 973X & Online: ISSN 0974 – 9624, Issue : November 2011, PDCS112011008.
- [25] Rajesh, M., and J. M. Gnanasekar. “Congestion control in heterogeneous wireless ad hoc network using FRCC.” *Australian Journal of Basic and Applied Sciences* 9.7 (2015): 698-702.
- [26] P. SIVA SANKAR, “A Secure and Fast Authentication implementation between the Entities using Trust Aware Algorithm”, *International Innovative Research Journal of Engineering and Technology*. ISSN NO:2456-1983, September 2016.34-40.

