

DESIGN EVALUATION AND ANALYSIS OF TWO WHEELER SUSPENSION HELICAL COMPRESSION SPRING

¹S.Ramesh Kumar, ²M.Rajesh, ³S.Kamalakkannan, ⁴M.Mohankumar, ⁵K.Prabu, ⁶R.Hariharan

^{1,2}Assistant Professor, Department of Mechanical Engineering, Karpagam college of Engineering, Coimbatore, Tamilnadu, India

^{3,4,5,6}UG Student, Department of Mechanical Engineering, Karpagam college of Engineering, Coimbatore, Tamilnadu, India
srkkce@gmail.com

Abstract: The primary elements of car suspension frameworks are to confine the structure. Because of vibration inhabitant feel awkward amid riding. The primary reason is failure to scatter stun or vibration of material. The present work is done on demonstrating, investigation and testing of suspension spring by supplanting the existed steel helical spring utilized as a part of well-known bike vehicle with new material. The testing model is utilized to test the spring under various stacking conditions. Among the different spring material Monel metal would give preferable stun assimilation over others.

Keywords: Coil Springs, Primary Suspension System, Modeling, Static Analysis, ANSYS 15.0, Pro-E.

1. Introduction

Suspension is the term given to the framework of springs, shock absorbers and linkages that associates a vehicle to its wheels. Suspension frameworks fill a double need adding to the auto's road holding/handling and braking for great dynamic security and driving joy, and keeping vehicle inhabitants agreeable and sensibly very much secluded from street commotion, knocks, and vibrations, and so on. These objectives are by and large at chances, so the tuning of suspensions includes finding the correct trade off. It is vital for the suspension to keep the street wheel in contact with the street surface however much as could reasonably be expected, in light of the fact that every one of the powers following up on the vehicle do as such through the contact patches of the tires. The suspension likewise secures the vehicle itself and any payload or baggage from harm and wear. The results of this are dynamic in the vehicles we see today. In like manner, at one extraordinary are huge car and extravagance autos with superb ride qualities however just acceptable taking care of conduct. On the last end of the range are sports autos with great dealing with yet firm ride quality. In the middle of is any number of

varieties managed by the vehicle producer and target client needs. Every car suspension has two goals: traveler solace and vehicle control. Solace is conveyed by disengaging the vehicles travelers from street aggravations like knocks or openings. Control is accomplished by keeping up the auto body from rolling and pitching to a great degree and keeping up great contact stuck between the tire and the street. All things considered, today's vehicle suspensions utilize pressure driven dampers and springs that are accused of the assignments of retaining knocks, diminishing the auto's body movements amid quickening, braking and turning and keeping the tires in contact with the street surface. A spring is characterized as a versatile body, whose capacity is to pack when stacked and to recuperate its unique shape when the heap is evacuated. A spring is an adaptable component used to apply a power or a torque and, in the meantime, to store vitality. The power can be a direct push or draw, or it can be spiral. The torque can be utilized to cause a turn. Springs can be arranged by the bearing and the idea of the drive applied by the spring when it is diverted. Helical pressure springs are normally produced using round wire, wrapped into a straight, round and hollow frame with a consistent pitch between neighboring loops. Square or rectangular wire may likewise be utilized. Without a connected load, the spring's length is known as the free length. At the point when a pressure compel is connected, the loops are squeezed all the more firmly together until they all touch, at which time the length the base conceivable is known as the strong length. A spring is characterized as a versatile body, whose capacity is to contort when stacked and to recuperate its unique shape when the heap is expelled. It is a versatile question used to store mechanical vitality. Springs are normally made out of spring steel. Little springs can be twisted from pre-solidified stock, while bigger ones are produced using tempered steel and solidified after creation. Some non-ferrous metals are additionally utilized including phosphor bronze and titanium for parts requiring consumption protection and beryllium copper for

springs conveying electrical current (on account of its low electrical protection). At the point when a spring is packed or extended, the power it applies is corresponding to its adjustment long. Helical springs are straightforward types of springs, ordinarily utilized for the suspension framework in wheeled vehicles. Vehicle suspension framework is made out of springs that have essential part in control exchange, vehicle movement and driving. Along these lines, springs execution advancement assumes imperative part in change of auto dynamic. The car business has a tendency to enhance the solace of client and achieve fitting equalization of solace riding qualities and economy. The helical springs are said to be firmly snaked when the spring wire is wound so shut that the plane containing each turn is about at right edges to the pivot of the helix and the wire is subjected to torsion. At the end of the day, in a firmly wound helical spring, the helix edge is little; it is generally under 10 degree. The significant anxieties created in helical springs are shear worries because of bending. The heap connected is parallel to or along the hub of the spring. In open wound helical springs, the spring wire is looped such that there is a hole between the two continuous turns, because of which the helix point is expansive. Helical springs are for the most part utilized as a part of two distinct applications. The first is the part of pressure spring which offers protection from powers moving two segments towards each other. Ordinary applications are auto suspension and matters spring. Pressure springs normally have their finishes end and taking into account simple mounting. The second normal use for helical spring is as a tensioning component. Springs utilized as a part of this part opposes powers moving in two protests from each other. Two or three basic pressure spring applications incorporate spring scales and programmed entryway closers. High-carbon spring steels are the most generally utilized of all springs materials. This material is liked to others since they are slightest costly, promptly accessible, effectively worked, and generally well known.

These materials are not attractive for high or low temperatures or for stun or affect stacking. Likewise this is the broadly useful spring steels and should just be utilized where life exactness and diversion are not very critical. This is best Analysis of Helical Compression Spring for Two Wheeler Automotive Rear Suspension suited for effect and stun stacking conditions. Car springs need to confront high working anxieties. The basic unwavering quality of the spring must hence be guaranteed. So for this reason the static pressure examination utilizing limited component technique has been done to discover the nitty gritty pressure appropriation of the spring. To expand life set up of present spring co-hub (arrangement) spring is dissected. Additionally factors influencing exhaustion life of this pressure spring are expressed hub

(arrangement) spring is examined. Likewise factors influencing weariness life of this pressure spring are expressed. Then again, plan can include choosing another material having a superior mix of attributes for a particular application; decision of material can't be made without thought of vital assembling forms (i.e., framing, welding, and so on.), which additionally depend on material properties. Or then again, at long last, outline may mean building up a procedure for delivering a material having better properties. Diminishment in weight is a need of car industry. In this manner the springs are to be intended for higher worries with little measurements. This requires basic plan of loop springs. This prompts basic material and assembling forms. Blend of springs with steel and composite material i.e. Glass fiber epoxy sap is to be utilized as a part of place of traditional spring steel. The vehicle taking care of turns out to be extremely troublesome and prompts awkward ride when bobbing is permitted uncontrolled. Henceforth, the planning of spring in a suspension framework is extremely significant. The examination is finished by considering bicycle mass, loads, and no of people situated on bicycle. Correlation is finished by differing the wire width of the loop spring to confirm the best measurement for the spring in safeguard. Displaying and Analysis is finished utilizing Pro/ENGINEER and ANSYS separately. The outline and adjustment of the suspension framework and dissecting that might it be able to be supplanted one overwhelming obligation spring in the place of twofold springs. Helical pressure springs are by and large used to assimilate the vitality because of the effects and to shape an adaptable connection which diverts under stacking and reestablish the items to the typical position where the irritating powers are evacuated. These springs for the most part in the suspension arrangement of two wheelers (motor bicycles) may flop because of over-burdening which happens in Indian conditions. Automobile producers today are confronting difficulties to decrease the assembling and support costs without affirming the quality and usefulness of parts.

Helical pressure springs contribute significantly in the aggregate expenses and weight of the suspension framework and are in this way subject for alteration change in plan.

The present work endeavor to investigate the outline of a spring utilized as a part of a bike vehicle with the destinations of looking at the conduct of steel material and composites utilized as spring materials.

2. Methodology

Various materials are used to carry out analysis on helical spring. The materials chosen are Monel, Inconel and Nickel: the specifications, modeling and analysis are as follows

2.1 Specifications of helical spring

Wire diameter = 9.39 mm,
Coil outer diameter = 55.94 mm,
Coil free height = 151 mm,
No. of active coils = 11,
Pitch = 13.6 mm,
Test load on each spring = 80 N , 160 N

2.2 Material property

For Monel metal properties are
Young's modulus = 1.79×10^5 MPa, Poisson ratio = 0.3,
Density = 8.08×10^{-12} kg/m³

For Inconel metal properties are Young's modulus
= 2.15×10^5 MPa, Poisson ratio = 0.29,
Density = 8.2×10^{-15} kg/m³

For Nickel metal properties are Young's modulus
= 2.07×10^5 MPa, Poisson ratio = 0.31, Density = 8.8×10^{-15} kg/m³

3. Modeling of Helical Spring

A loop spring is outlined by utilizing PRO-E according to the determinations and broke down by ANSYS 12.0 programming. In this the spring conduct will be seen by applying distinctive materials loads, to ideal anxieties and the outcome indicates best material. Model of the spring will be first made by utilizing PRO-E. Start by drawing a line of 152 mm length and it is the free stature of spring.



The helical spring which might be in pressure or strain. The real burdens delivered in this are shear because of turning. The heap connected is parallel to the pivot of spring. The cross-area of the wire might be round, square or rectangular. These springs are twisted as a helix of a wire.

2.3 Analysis of modeled helical coil spring


A model of the helical spring was made utilizing Pro/Engineer programming. At that point the model will be foreign made to investigation utilizing FEA utilizes an unpredictable arrangement of focuses called hubs which make a network called a work.

This work is customized to contain the material and basic properties which characterize how the structure will respond to certain stacking conditions.


Hubs are doled out at a specific thickness all through the material relying upon the expected feelings of anxiety of a specific territory. This model incorporates static investigation with various materials to ideal the anxieties.




Total Deformation (Monel)




Strain (Monel)




Strain (Inconel)




Stress (Monel)




Total Deformation (Inconel)




Total Deformation (Nickel)




Strain (Inconel)




Strain (Nickel)




Stress (Nickel)




Stress (Monel)




Total Deformation (Monel)




Total Deformation (Inconel)




Strain (Monel)




Strain (Inconel)




Stress (Inconel)



Total Deformation (Nickel)



Strain (Nickel)



Stress (Nickel)

3. Literature Review

For giving the best outline of spring curl to the suspension arrangement of bike vehicles. A ton of specialized papers and decrease forms were considered before settling on the most plausible process for venture.

The accompanying rundown exhibits a substance of the fundamental papers alluded to, all through the span of the project. The display work is ideal plan and examination of a suspension spring for engine vehicle subjected to static investigation of helical spring the work demonstrates the strain and strain reaction of spring conduct will be seen under endorsed or expected burdens and the actuated pressure and strains esteems for low carbon auxiliary steel is less contrasted with chrome vanadium material additionally it improves the cyclic weakness of helical spring.

By looking at the outcomes for show plan and adjusted outline, the pressure and dislodging esteems are less for changed outline. So they reasoned that according to our examination utilizing material spring steel for spring is ideal and furthermore their changed plan is sheltered.

The similar arrangement of the geometry like the distance across of the wire, the pitch, number of turns, and so on influence the Finite Element Modeling procedures offer knowledge into the idea of the anxieties, redirection or some other reaction parameter in charge of the execution of the spring. Execution of the spring in a great or unfriendly way. Reproduction utilizing investigation has been completed in the middle of the hypothetical esteems to the test esteems and the expository esteems.

The mechanical properties of the suspension spring alongside the Experimentation for weakness life isn't achievable in the greater part of the cases. The trial setup for recording firmness of the spring may be achievable for seeking after research further. The above writing audit shows that the helical pressure springs turns out to be very important to do the entire pressure examination of the spring.

These springs experience the fluctuating stacking over the administration life. Moreover, FEM programming has been use for performing fitting recreation. Nearly in the majority of the above cases, exhaustion push, shear pressure computation assume more huge part in the plan of helical pressure springs.

This examination demonstrates that shear pressure and avoidance condition is utilized for computing the quantity of dynamic turns and mean breadth in helical pressure springs. Examination of the hypothetical got result by the shear pressure condition to the Finite Element Analysis consequence of helical pressure springs is the method of our present work.

4. Result Comparison

Result comparison for 80 kg of load,

		MIN	MAX
Deflection (mm)	Monel	0	83.75
	Nickel	0	72.83
	Inconel	0	69.294
Strain (mm/mm)	Monel	3.638E-14	0.0131
	Nickel	3.04 E-14	0.0113
	Inconel	2.798E-14	0.0109
Stress	Monel	3.824 E-9	2225.9

Results comparison for 160kg load,

CATEGORY		MIN.	MAX.
Deflection (mm)	Monel	0	167.52
	Nickel 200	0	145.77
	Inconel	0	138.59
Strain (mm/mm)	Monel	6.412E-14	0.0262
	Nickel 200	5.38E-14	0.0226
	Inconel	4.920E-14	0.0218
Stress (mpa)	Monel	8.025E-9	4451.7

5. Cost of Material

MATERIALS	WEIGHT (Kg)	COST (Rs)	QTY
MONEL	1	400	1
INCONEL	1	800-2000	1
NICKEL	1	800	1

6. Conclusion

From the static auxiliary investigation the redirection esteem is contrasted and the hypothetical diversion esteem. It is specified that the Monel metal has low diversion than different materials, which infers it has great damping impact and its creation cost is low when contrasted and different materials.

References

- [1] Pinjarla.Poormohan and Lakshmana Kishore T, "Design and Analysis of a Shock Absorber", International Journal of Research in Engineering and Technology, ISSN: 2319-1163, Volume: 1, Issue: 4, pp.578-592, December 2012.
- [2] Kommalapati. Rameshbabu, Tippa Bhimasankar Rao, "Design Evaluation of a two wheeler suspension system for variable load conditions" International Journal of Computational Engineering Research, Vol 03, Issue 4, pp. 279-283 , 2013.
- [3] Gajendra Singh Rathore and Upendra Kumar Joshi, "Fatigue Stress analysis of helical Compression Spring: A Review", International Journal of Emerging Trends in Engineering and Development, ISSN: 2249-6149, Volume: 2, Issue: 3, pp. 512-520, May 2013.
- [4] Saurabh Singh- "Optimization of Design of Helical Coil Suspension System by Combination of Conventional Steel and Composite Material in Regular Vehicle" International Journal of Applied Engineering Research, ISSN 0973-4562 Vol.7 No.11 (2012).
- [5] Becker L.E., G.G.Chassies:- " On the Natural frequencies of helical compression springs" L.E. Becker et al. / International Journal of Mechanical Sciences 44 (2002) 825–841.
- [6] Y. Prawoto, M. Ikeda , S.K. Manville, A. Nishikawa, "Design and failure modes of automotive suspension springs", Engineering Failure Analysis 15 (2008) 1155–1174.
- [7] B. Pyttel, I. Brunner, B. Kaiser, C. Berger, M. Mahendran (2013), "Fatigue behavior of helical compression springs".
- [8] T.Padmapriya and V.Saminadan, "Utility based Vertical Handoff Decision Model for LTE-A networks", International Journal of Computer Science and Information Security, ISSN 1947-5500, vol.14, no.11, November 2016.
- [9] S.V.Manikanthan and D.Sugandhi "Interference Alignment Techniques For MIMO Multicell Based On Relay Interference Broadcast Channel" International Journal of Emerging Technology

in Computer Science & Electronics (IJETCSE) ISSN: 0976-1353 Volume- 7, Issue 1 –MARCH 2014.

[10] Rajesh, M., and J. M. Gnanasekar. "An optimized congestion control and error management system for OCCEM." International Journal of Advanced Research in IT and Engineering 4.4 (2015): 1-10.

[11] N.Prathima, K.Hari Kishore, "Design of a Low Power and High Performance Digital Multiplier Using a Novel 8T Adder", International Journal of Engineering Research and Applications, ISSN: 2248-9622, Vol. 3, Issue.1, Jan-Feb., 2013.

