

A FUSION OF IMAGE PROCESSING AND NEURAL NETWORKS FOR LUNG CANCER DETECTION USING SVM IN MATLAB

¹Ranjani.R and ²Dr.C. Priya

¹Research Scholar,
School of Computing Sciences,
VELS Institute of Science, Technology and Advanced Studies (VISTAS), Chennai.
ranji010794@gmail.com

² Research Supervisor,
Associate Professor,
School of Computing Sciences,
Department of Information Technology,
VELS Institute of Science, Technology and Advanced Studies (VISTAS), Chennai.
drcpriya.research@gmail.com

1. ABSTRACT

Lung Cancer is ended up being a cataclysmic danger to the humankind and is fundamental driver of passing among other tumor related losses. The nearness of singular pneumonic knobs in human lungs as generous or threatening decides the gravity of lung disease. In this paper, a novel technique for lung knob recognition, division and arrangement utilizing Computed Tomography (CT) pictures is displayed. A standout amongst the most well-known clamors in CT imaging is a drive commotion which is caused by shaky voltage. In this paper, another choice based system called new adaptive median filter is displayed which indicates preferable execution over those as of now being utilized. The CT slices are at first preprocessed to expel the Gaussian clamor by utilizing Gaussian channel. Otsu thresholding is connected to extricate the Region of Interest

(ROI). We have the diverse arrangements about the knobs in the lung. It contains the diverse strategy for characterization, division and identification strategies. Cancer cell displayed in the lungs named, knobs are characterized for the treatment forms. In the last advance, we arrange the knob hopeful pictures into knobs and non-knobs. We separate element vectors of the items in the chose squares. In conclusion, the support vector machine (SVM) is connected to arrange the extracted highlight vectors. The SVM will arrange the images into ordinary or unusual in view of the second order Gray Level Co-Occurrence Matrix Feature (GLCM).

KEYWORDS: Computed Tomography (CT), new adaptive median filter, Region Of Interest (ROI), Support Vector Machine (SVM), Gray Level Co-occurrence Matrix Features. (GLCM)

2. INTRODUCTION

Computer supports the findings of lung CT picture has been a progressive advance in the early diagnosing of lung infections. The best technique for actualizing PC supported conclusion for therapeutic picture examination is first to preprocess the picture with a specific end goal to portion it. The initial phase in computers helped conclusion of lung figured tomography understanding picture is by and large to first portion the locale of enthusiasm, for this situation lung, and afterward examine independently every region got, for a tumor, disease, hub identification or other pathology for finding. This is for the most part considerably less demanding methodology, on the grounds that the zone

utilized for setting the correct conclusion, is getting littler with the procedure of division, so the radiologist can concentrate his perception just on particular information inside the particular district. In this paper we proposed lung division procedure to precisely portion the lung parenchyma of lung CT pictures, which can help radiologist in early diagnosing lung ailments, however the calculation can likewise be utilized to early analyze other benevolent or dangerous pathologies in different organs, for example, liver, cerebrum or spine.

Types of Lung Diseases

- Lung Diseases affecting the airways;
- Lung Diseases affecting the air sacs (Alveoli);
- Lung Diseases affecting the Interstitium;
- Lung Diseases affecting blood Vessels;
- Lung Diseases Affecting the Pleura;
- Lung Diseases Affecting the Chest Wall.

3. Related Work

Hierarchical Vector Quantization Scheme

Computed aided detection (CAdE) of pneumonic knobs is basic to helping radiologists in early recognizable proof of lung tumor from computed tomography (CT) examines. This paper proposes a novel CAdE framework in view of a progressive vector quantization (VQ) plot. Contrasted and the regularly utilized straightforward thresholding approach,

the abnormal state VQ yields a low precise division of the lungs from the chest volume. In recognizing initial nodule candidates (INCs) inside the lungs, the low-level VQ turns out to be viable for INCs location and division, and additionally computationally effective contrasted with existing methodologies. False-positive (FP) diminishment is directed by means of manage based sifting operations in blend with an element based help vector machine

Classifier. In areas such, for example, PC vision and picture preparing, picture division has been and still is a pertinent research territory because of its far reaching utilization and application. This paper gives a review of accomplishments, issues being experienced, and the open issues in the exploration territory of picture division and use of the systems in various regions. We thought about the systems under the accompanying three gatherings: Threshold-based, Edge-based and Region-based.

Vector Quantization is a way to deal with picture division in which neighboring pixels are inspected and added to an area class if no edges are recognized. This procedure is iterated for every limit pixel in the district.

4. Methodologies


In this paper, we present a non-rigid registration-driven robust lung segmentation method using edge based patient specific adaptive lung models that detects lung boundaries, surpassing state-of-the-art performance. The method consists of three main stages: 1) lung image preprocessing with hybrid median filter 2) lung image enhancement using adaptive mean adjustment for contrast stretching 3) Lung image cancer segmentation using active shape model.

DISADVANTAGES OF HVQSM ALGORITHM

- The vector quantization is not preferred for its limited range of applications and automatic features are not having accurate values.
- Pre-processing experiments are needed to find which type of filtering will be more beneficial. This increases the effect of the speckle noise and Gaussian noise the CT Images.
- The desired cancer area is selected from the segmented image to calculate the volume. The volume of the desired cancer area is greater than the original cancer area. The region growing algorithm will segment not only the tumor area but also the non tumour area which has high intensity ratio.
- This algorithm fully depends on the intensity of the image not the shape and texture. So the accuracy and sensitivity is low

1. Image restoration using New Adaptive Median Filter
2. Image enhancement using adaptive Mean adjustment
3. Heuristic Approach for Lung Nodule Segmentation
4. Feature Extraction
5. Classification using SVM (Support Vector Machine)

BLOCK DIAGRAM



1. New Adaptive Median filter

The CT image contains impulse noise of voltage of the CT image scanners. This clamor can be wiped out utilizing New Adaptive Median Filter. The Hybrid Median filtering is like an averaging filter, in that each yield pixel is set to a normal of the pixel esteems in the area of the comparing input pixel. Be that as it may, with middle sifting, the estimation of a yield pixel is controlled by the middle of the area pixels, as opposed to the mean. The middle is considerably less delicate than the intend to outrageous esteems (called outliers). New Adaptive Median filtering is in this way better ready to expel these exceptions without diminishing the sharpness of the image. Therefore the adaptive median filtering has been connected generally as a propelled technique contrasted and standard median filtering. The Adaptive Median Filter performs spatial

handling to figure out which pixels in a image have been influenced by motivation commotion. The Adaptive Median Filter orders pixels as commotion by contrasting every pixel in the picture with its encompassing neighbor pixels. The span of the area is flexible, and also the limit for the correlation. A pixel that is not quite the same as a larger part of its neighbors, and additionally being not fundamentally lined up with those pixels to which it is comparable, is named as impulse noise. These commotion pixels are then supplanted by the middle pixel estimation of the pixels in the area that have breezed through the noise labeling test.

Purpose

- 1) Remove impulse noise
- 2) Smoothing of other noise
- 3) Reduce distortion, like excessive thinning or thickening of object boundaries

2. Image enhancement using Mean Adjustment

In Image enhancement, the histogram is cut at some limit and after that leveling is connected. Balance Image upgrade with mean alteration is a adaptive contrast histogram technique, where the difference of a image is improved by applying the calculation on little information locales called tiles instead of the whole picture. The subsequent neigh-exhausting tiles are then sewed back consistently utilizing bi linear introduction. The contrast in the homogeneous region can be constrained so commotion intensification can be stayed away from.

Different enhancement plans are utilized for improving a picture which incorporates gray scale control, filtering and Histogram Equalization (HE). Histogram equalization is one of the notable image enhancement method. It turned into a

popular strategy for contrast enhancement since this technique is basic and compelling. In the last case, saving the info brilliance of the picture is required to maintain a strategic distance from the age of non-existing antiquities in the yield image. In spite of the fact that these strategies protect the information splendor on the yield image with a noteworthy complexity upgrade, they may create pictures with don't look as normal as the info ones. The essential thought of HE strategy is to re-delineate dark levels of a image. HE has a tendency to present some irritating relics and unnatural upgrade. To beat these downsides distinctive brilliance saving methods are utilized which are shrouded in the writing reviews.

Contrast

Contrast characterizes the difference among most reduced and highest intensity level. Higher the estimation of contrast implies more difference between most minimal and highest intensity level.

3. Heuristic Approach for Lung Nodule Segmentation

Heuristic approach is utilized widely for lung image division and handling applications, especially to find disease limits. Heuristic approach is viewed as promising and enthusiastically inquired about model-based way to deal with computer assisted medical image examination. A Heuristic approach division plot is exhibited that is controlled by optimal local features, as opposed to standardized first order derivative profiles, as in the first definition. A nonlinear classifier is utilized, rather than the direct Mahalanobis separate, to discover ideal removals for points of interest. For each of the points of interest that depict the shape, at every determination level considered amid the division advancement methodology, an unmistakable arrangement of ideal features is resolved. The determination of features is programmed, utilizing the preparation images and consecutive component forward and in reverse choice.

Image segmentation:

To people, a image isn't only an irregular accumulation of pixels; it is an important plan of districts and protests. There additionally leaves an assortment of pictures: common scenes, sketches, and so on. Notwithstanding the huge varieties of these pictures, people have no issue to translate them. Thinking about the expansive databases on the WWW, in our own photo organizers, a solid and programmed picture examination would be welcome.

Image segmentation is the initial phase in image investigation and example acknowledgment. It is a basic and basic segment of picture investigation framework, is a standout amongst the most troublesome errands in image handling, and decides the nature of the last consequence of examination. Picture division is the way toward separating a

image into various regions with the end goal that every locale is homogeneous.

The segmentation of imaging information includes apportioning the image space into various bunch regions with comparative power image esteems. The most medical images constantly introduce covering dim scale powers for various tissues. Thusly, fuzzy clustering strategies are especially reasonable for the division of restorative pictures. There are a few FCM clustering applications in the lung segmentation. The Fuzzy c-means (FCM) can be viewed as the fuzzified rendition of the k-means calculation. It is a strategy for clustering, which enables one bit of information to have a place with at least two groups. This strategy is much of the time utilized as a part of example acknowledgment. The calculation is an iterative clustering technique that delivers an optimal c segment by limiting the weighted inside gathering entirety of squared error objective function. Image segmentation was, is and will be a noteworthy research point for some, image

Handling specialists. The reasons are evident and applications perpetual: most computer vision and image investigation issues require a division arrange with a specific end goal to identify questions or separation the picture into districts which can be viewed as homogeneous as indicated by a given standard, for example, shading, movement, surface, and so on.

Clustering is the scan for unmistakable groups in the feature space. It is normal that these gatherings have diverse structures and that can be unmistakably separated. The clustering task isolates the information into number of parcels, which are volumes in the n-dimensional element space. These parcels characterize a hard cutoff between the diverse gatherings and rely upon the capacities used to display the information dissemination

3. A given edge in the picture should just be stamped once, and where conceivable, picture commotion ought not make false edges.

To fulfill these necessities Canny utilized the analytics of varieties – a strategy which finds the capacity which enhances a given useful. The ideal capacity in Canny's indicator is portrayed by the whole of four exponential terms, however it can be approximated by the main subsidiary of a Gaussian. Among the edge recognition techniques grew up until now, Canny edge discovery calculation is a standout among the most entirely characterized strategies that gives great and solid identification. Attributable to its optimality to meet with the three criteria for edge location and the effortlessness of process for usage, it wound up plainly a standout amongst the most well-known calculations for edge discovery.

OTSU Thresholding Algorithm:

The algorithm assumes that the image contains two classes of pixels following bi-modular histogram (frontal area pixels

CANNY EDGE DETECTION:

Canny edge detection is a strategy to extract valuable auxiliary data from various vision objects and drastically decrease the measure of information to be prepared. It has been generally connected in different computer vision frameworks. Canny has discovered that the prerequisites for the utilization of edge recognition on various vision frameworks are moderately comparative. In this manner, an edge detection answer for address these necessities can be executed in an extensive variety of circumstances. The general criteria for edge recognition include:

1. Detection of edge with low blunder rate, which implies that the identification ought to precisely get whatever number edges appeared in the picture as could be allowed
2. The edge point distinguished from the administrator ought to precisely limit on the focal point of the edge.

and foundation pixels), it at that point computes the optimal limit isolating the two classes with the goal that their joined spread (intra-class variance) is insignificant, or comparably (on the grounds that the aggregate of combine savvy squared separations is steady), so their between class change is maximal. Therefore, Otsu's technique is approximately a one-dimensional, discrete simple of Fisher's Discriminant Analysis. Otsu's thresholding technique includes emphasizing through all the conceivable edge esteems and ascertaining a measure of spread for the pixel levels each side of the edge, i.e. the pixels that either fall in closer view or foundation. The point is to discover the edge esteem where the total of frontal area and foundation spreads is at its base.

K-Means clustering creates a particular number of disjoint, level (non-various leveled) bunches. It is appropriate to creating globular groups. The K-Means strategy is numerical, unsupervised, non-deterministic and iterative.

4. Feature Extraction using Gray level co-occurrence Matrix

It is a statistical strategy that considers the spatial relationship of pixels is the gray-level co-occurrence matrix (GLCM), also known as the gray-level spatial dependence matrix. . As a matter of course, the spatial relationship is characterized as the pixel of intrigue and the pixel to its quick right (on a level plane adjoining), however you can determine other spatial connections between the two pixels. Every component (I, J) in the resultant GLCM is essentially

5. Classification using SVM

This research paper proposes an smart arrangement method to perceive ordinary and unusual mammogram picture. Medicinal images like ECG, MRI and CT-check, mammogram pictures are vital approach to analyze sickness of person effectively. The manual investigation of tumor in view of visual examination by radiologist/doctor is the regular technique, which may prompt wrong characterization when an expansive number of Mammogram are to be dissected. To dodge the human blunder, a mechanized smart arrangement framework is proposed which cooks the requirement for characterization of picture. One of the real reasons for death among individuals is Brain tumor. The odds of survival can be expanded if the tumor is recognized effectively at its beginning period. Mammogram technique is utilized for the investigation of the

K-Means Algorithm Algorithm steps:


1. Compute histogram and probabilities of every intensity level.
2. Set up introductory class likelihood and beginning class implies.
3. Step through every single conceivable limit most extreme power.
4. Update q_i and μ_i .
5. Compute between class variance .
6. Desired limit compares to the most extreme estimation of between class variance

the aggregate of the circumstances that the pixel with esteem I happened in the predefined spatial relationship to a pixel with esteem J in the information picture.

The following GLCM highlights were extricated in our examination work: Autocorrelation, Contrast, Correlation, Cluster Prominence, Cluster Shade, Dissimilarity Energy, Entropy, Homogeneity, Maximum likelihood , Sum of squares, Sum normal, Sum change, Sum entropy, Difference fluctuation, Difference entropy, Information measure of connection, data measure of relationship, Inverse distinction standardized.

human cerebrum. In this examination work, order procedures in light of Support Vector Machines (SVM) are proposed and connected to mind picture characterization. In this paper include extraction from mammogram Images will be done by dark scale, symmetrical and surface highlights. The principle target of this paper is to give a brilliant result (i.e. higher exactness rate and lower mistake rate) of mammogram malignancy disease order utilizing SVM. Machine Learning is considered as a subfield of Artificial Intelligence and it is worried about the improvement of procedures and techniques which empower the PC to learn. In straightforward terms improvement of calculations which empower the machine to learn and perform undertakings and exercises. Machine learning covers with measurements from multiple points of view. Over the timeframe numerous procedures and systems were produced for machine learning errands. Right off the bat working with neural systems for administered and unsupervised learning demonstrated great

outcomes while utilized for such learning applications. MLP's uses encourage forward and repetitive systems. Multilayer perceptron (MLP) properties incorporate general estimate of nonstop nonlinear capacities and incorporate learning with input-yield designs and furthermore include propelled arrange models with different information sources



and yields.

a) Simple Neural Network

5. RESULTS & DISCUSSION:

The proposed system was tested with 20 CT Scan Images of different patients.

Steps Followed to obtain the Results.

Step 1: Any 1 image from the Dataset is acquired and displayed.

Step 2: The acquired colored image in RGB form is converted into Grayscale image.




Figure 1: b) Multilayer Perceptron.

Step 3: The converted Grayscale Image is filtered using New Adaptive Median Filter by using Hybrid Median Filter

Step 4: The filtered image is enhanced to remove unwanted noise and obtain the contrast and brightness.




Figure A: Image Pre-Processing

These are basic representations just to have a diagram as how neural system resembles. There can be a few issues took note. Some of them are having numerous nearby minima and furthermore discovering what number of neurons may be required for an assignment is another issue which decides if optimality of that NN is come to. Something else to note is that regardless of whether the neural system arrangements utilized has a tendency to unite, this may not bring about a special arrangement. Presently let us take a gander at another illustration where we plot the information and endeavor to characterize it and we see that there are numerous hyper planes which can order



Figure B: Image Segmentation

Step5: The enhanced image is segmented in 3 steps:

- 1) Canny Edge Detection
- 2) OTSU Thresholding
- 3) K-means Clustering

Step 6: After segmenting the image by applying the above 2 steps, the 2 images are clubbed/Mapped to obtain a edged and thresholder image as shown in Figure B

Step 7: The image is clustered using K-means clustering algorithm to obtain the ROI(Region of Interest) that is the final segmented image as shown in Figure C




Figure C: Image Segmentation 2 to obtain ROI





Figure D: Neural Network (SVM)

Table 1: Performance Comparison

PARAMETERS	HVQSM	SVM
ACCURACY	88.5%	92.8%
SENSITIVITY	87.2%	99.2%
SPECIFICITY	3.5%	5.7%

Step 8: The ROI/Final segmented image is used to obtain the features for training and testing using SVM classification. The Features are extracted by using GLCM (Gray-Level Co-occurrences Matrix).

Step 9: Once the features are obtained using GLCM, SVM classification is applied using **newcf (new cascaded feed forward network)** for testing and training.

Step 10: The tested and trained output obtained through SVM classifies the output into 2 classes

1) ABNORMAL CLASS-Cancer Detected 2) NORMAL CLASS-Cancer not detected.

Step 11: Once the class is detected we can obtain the difference between the existing and proposed system using ROC Curve as shown in Figure E. The proposed system shows more than 90% accuracy that is 10% more accurate than existing system.




Figure E :ROC Curve

6. CONCLUSION:

In this paper, a novel CAde framework was proposed for quick and versatile discovery of pneumonic knobs in lungCT filters. In this examination, basic master rules were right off the bat utilized to reject clear from being considered by the modern component based SVM classifier. The SVM order comes about demonstrated that inclination highlights contributed the most against any of the other three gatherings of the highlights (geometric, force, and Hessian highlights). The forward component choice procedure demonstrated that the SVM classifier played out the best in the "slope + power" include space as opposed to for some other element blends. Contrasted and existing CAde frameworks assessed on a similar lung picture LIDC database, our approach demonstrated a tantamount identification capacity however a lower computational cost. Specifically, we revealed the execution of our framework for the recognition of juxtapleural knobs. The proposed framework discovery approach

is quick, versatile, and completely programmed. The exhibited CAdE framework yields practically identical identification precision and more computational proficiency than existing frameworks, which shows the attainability of

our CAdE framework for clinical utility. In this way this paper introduces a combination of picture preparing and neural system methods of the given CT Dataset Images to recognize lung tumor utilizing mat lab programming

7. ACKNOWLEDGMENT:

My sincere thanks and gratitude for school of Computing Sciences, Vels University, ICIRTCTA'18, Easy chair for

8. REFERENCES:

- [1] Hao Han, Lihong Li, Fangfang Han, Bowen Song, William More and Zhengrong Liang, "Fast and Adaptive Detection of Pulmonary Nodules in Thoracic CT Images Using a Hierarchical Vector Quantization Scheme", IEEE Journal of Biomedical and Health Informatics, Vol 19, No: 2, March 2015.
- [2] Aniketbommbale, C.G.Patil, "SEGMENTATION OF LUNG NODULE IN CT DATA USING K-MEAN CLUSTERING", International Journal of Electrical, Electronics and Data Communication, ISSN: 2320-2084 Volume-5, Issue-2, Feb.-2017.
- [3] Resmi R. Nair¹, B. Thamilvalluvan¹, M. Anto Bennet², P. Lavanya³, S. Ragavi³, and S. Arun Kumar³, "Early Detection of Pulmonary Nodules Using Hierarchical Vector Quantization Scheme", International Journal of Innovation and Scientific Research ISSN 2351-8014 Vol. 22 No. 2 Apr. 2016, pp. 431-438.
- [4] N. Bala Sundara Ganapathy¹, B. Naresh Kumar², K. Prabhakaran³, S. Praveen⁴, P. Jayaseelan, "Detection of Pulmonary Nodules in Thoracic CT Images Using A HVQ Scheme", International Journal of Engineering Science and Computing, March 2016, ISSN 2321 3361, Volume 6 Issue No. 3
- [5] Capt. Dr. S. Santhoshbaboo and E. Iyyaparaj, "A Study On Fast Adaptive Detection of Pulmonary Nodules in Thoracic CT Images Using a Hierarchical Vector Quantization Scheme", International Journal of Innovative Research in Information Security (IJIRIS) ISSN: 2349-7017(O) Issue 06, Volume 3 (September 2016).
- [6] Swathi H K and Nanda S, "Detection of Lung Nodules From CT Images using Image Processing Techniques", International Conference on Signal, Image Processing Communication and Automation - ICSIPCA-2017
- [7] Karthika.K^{*1}, Sandhya.P², T. Thaj Mary Delsy³, "ADAPTIVE DETECTION OF PULMONARY NODULES IN CT IMAGES BY SEGMENTATION AND CLASSIFICATION USING MATLAB", International Journal Of Pharmacy & Technology, ISSN: 0975-766X, IJPT June-2016 | Vol. 8 | Issue No.2 | 11980-11985
- [8] Bhavanishankar .K¹ and Dr. M.V.Sudhamani², "TECHNIQUES FOR DETECTION OF SOLITARY PULMONARY NODULES IN HUMAN LUNG AND THEIR CLASSIFICATIONS -A SURVEY", International Journal on Cybernetics & Informatics (IJCI) Vol. 4, No. 1, February 2015.
- [9] H. Mahersia, M. Zaroug and L. Gabralla, "Lung Cancer Detection on CT scan Images: A Review on the Analysis Techniques", (IJARAI) International Journal of Advanced Research in Artificial Intelligence, Vol. 4, No.4, 2015.
- [10] Sheila Ramaswamy and Karen Truong, "Pulmonary Nodule Classification with Convolutional Neural Networks
- [11] A. El-Baz and et al. Computer-aided diagnosis systems For lung cancer: Challenges and methodologies. International Journal of Biomedical Imaging, 2013, 2013.
- [12] T. Messay, R. C. Hardie, and S. K. Rogers, "A new Computationally efficient CAD system for pulmonary Nodule detection in CT imagery," Med. Image Anal., vol. 14, no. 3, pp. 390-406, 2010.
- [13] M. Tan, R. Deklerck, B. Jansen, M. Bister, and J. Cornelis, "A novel computer-aided lung nodule Detection system for CT images," Med. Phys., vol. 38, No. 10, pp. 5630-5645, 2011.
- [14] Siegel R, Naishadham D, Jemal A. Cancer statistics. CA Cancer J. Clin. 2013; 63:11-30.
- [15] Teramoto A, Fujita H. Fast lung nodule detection in Chest CT images using cylindrical nodule-enhancement Filter. Int. J. CARS. 2013; 8:193-205.

Imparting me all of the trying out centers to carry out my work successfully.

- [16] Tan M, Deklerck R, Jansen B, Bister M, Cornelis J. A Novel computer-aided lung nodule detection system For CT images. *Med. Phys.* 2011; 38:5630–5645.
- [17] Chang C-C, Lin C-J. LIBSVM: A library for support Vector machines. *ACM Trans. Intell. Syst. Technol.* 2011; 2(27).
- [18] Armato SG, et al. The lung image database consortium (LIDC) and image database resource initiative (IDRI): A Complete reference database of lung nodules on CT Scans. *Med. Phys.* 2011; 38:915–931.
- [19] Gomathi M, Thangaraj P: Computer aided medical Diagnosis system for detection of lung cancer nodules: a survey. *Int J ComputIntell Res* 2009, 5:453–467.
- [20] Ada et al., "Feature Extraction and Principal Component Analysis for Lung Cancer Detection in CT Scan Images". *International journal of Advanced Research in Computer Science and Software Engineering*, Vol. 3. 2013.
- [21] Sunil Kumar et al., "Lung Segmentation using Region Growing Algorithm", *International Journal of Advanced Research in Computer Science and Software Engineering* Volume 4. 2014.
- [22] Mr.Vijay A.Gajdhane, "Detection of Lung Cancer Stages on CT scan Images by Using Various Image Processing Techniques ", ISSN: 2278-8727, Volume 16, Issue 5, Ver. III, PP 28-3, Sep – Oct. 2014
- [23] M. Tan, R. Deklerck, B. Jansen, M. Bister, and J. Cornelis, "A novel computer-aided lung nodule detection system for CT images," *Med.Phys.*, vol. 38, no. 10, pp. 5630–5645, 2011.
- [24] J. Dehmeshki, X. Ye, X. Lin, M. Valdivieso, and H. Amin, "Automated detection of lung nodules in CT images using shape-based genetic algorithm," *Comput. Med. Imag. Graph.* vol. 31, pp. 408–417, 2007.
- [25] Gori, I., Bellotti, R., Cerello, P, et al.: "Lung nodule Detection in screening computed tomography", *IEEE Nuclear Science Symposium Conference Record*. IEEE (2006)
- [26] I. Sluimer, A. Schilham, M. Prokop, and B. V. Ginneken, "Computer analysis of Computed Tomography scans of the lung: A Survey", *IEEE Trans. on Medical Imaging*, vol. 25, pp 385-405, 2006.
- [27] Early Lung Cancer Action Program (ELCAP): <http://via.cornell.edu/lungdb.html>
- [28] Lung Image Database Consortium (LIDC): <https://imaging.nci.nih.gov/ncia/login.jsf>
- [29] Medical Image Database: MedPix : <http://rad.usuhs.edu/medpix/index.html>
- [30] G. Vijaya and A. Suhasini, An Adaptive Pre-Processing of Lung CT Images with Various Filters For Better Enhancement, *Academic Journal of Cancer Research*, Vol. 7, No. 3, pp. 179-184, 2014.

